

# GENIE SAKSELIFTE, SELVSTYRENDE, HÅRDT TERRÆN GS-4390 RT FORD LRG- 425EFI (42686 -) (2008 OG EFTER)



**MOTOR** Ford LRG-425 EFI  
Kapacitet: 4,3 liter

| ANVEND | KLIMA            |
|--------|------------------|
| Normal | Middelhavsagtigt |

PRODUKTANBEFALING 1

**Synfleet SHPD 10W-40**

Kontroller alle 10 timer, skift alle 200 timer

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

PRODUKTANBEFALING 1

**Asyntho 5W-30**

Kontroller alle 10 timer, skift alle 200 timer

## NAVREDUKTIONER

Kapacitet: 0,77 liter (hvert nav)

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

PRODUKTANBEFALING 1

**Gearlube GL-5 80W-90**

PRODUKTANBEFALING 2

**Unigear HS GL-3/GL-5 80W-90**

Kontroller alle 250 timer, skift alle 1000 timer/ 12 måneder

| ANVEND           | KLIMA   |
|------------------|---------|
| Første skift kun | Moderat |

PRODUKTANBEFALING 1

**Gearlube GL-5 80W-90**

PRODUKTANBEFALING 2

**Unigear HS GL-3/GL-5 80W-90**

Skift alle 150 timer

## HYDRAULISK SYSTEM

Kapacitet: 114 liter (Hydrauliktank), Kapacitet: 144,8 liter (System, med udliggere), Kapacitet: 132,5 liter (System, uden udliggere)

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

PRODUKTANBEFALING 1

**SP Matic 2032**

PRODUKTANBEFALING 2

**ATF Almirol**

Kontroller alle 250 timer, skift alle 2000 timer/ 24 måneder

| ANVEND                  | KLIMA   |
|-------------------------|---------|
| Alternativ (acceptabel) | Moderat |

PRODUKTANBEFALING 1

**Perlus H 46**

PRODUKTANBEFALING 2

**Perlus H 32**

PRODUKTANBEFALING 3

**Perlus AF 46**

Kontroller alle 250 timer, skift alle 2000 timer/ 24 måneder

# GENIE SAKSELIFTE, SELVSTYRENDE, HÅRDT TERRÆN GS-4390 RT FORD LRG- 425EFI (42686 -) (2008 OG EFTER)



## SMØREPUNKTER/NIPLER

| ANVEND               |                                 | KLIMA                        |
|----------------------|---------------------------------|------------------------------|
| Normal               |                                 | Moderat                      |
| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

## KØLESYSTEM

Kapacitet: 10,9 liter

| ANVEND                        |                     | KLIMA   |
|-------------------------------|---------------------|---------|
| Normal                        |                     | Moderat |
| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2 |         |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>  |         |

*Kontroller alle 10 timer, skift alle 800 timer*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*