

GENIE SPOREDE SKOVANHÆNGERE GTH/AGRI GTH-4017 (10645 -> 19295) - PERKINS 1104C-44T



MOTOR Perkins 1104C-44T
Kapacitet: 11,5 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40

Kontroller alle 8 timer, skift alle 12 måneder/ 500 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Armado Synth 5W-30

Kontroller alle 8 timer, skift alle 12 måneder/ 500 timer

ANVEND	KLIMA
Krævende	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40

Kontroller alle 8 timer, skift alle 12 måneder/ 250 timer

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Armado Synth 5W-30

Kontroller alle 8 timer, skift alle 12 måneder/ 250 timer

DIFFERENTIALE BAG
Kapacitet: 8,7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

Kontroller alle 250 timer, skift alle 1000 timer/ 12 måneder

DIFFERENTIALE FOR
Kapacitet: 8,7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

Kontroller alle 250 timer, skift alle 1000 timer/ 12 måneder

GENIE SPOREDE SKOVANHÆNGERE GTH/AGRI GTH-4017 (10645 -> 19295) - PERKINS 1104C-44T



GEARKASSE

Kapacitet: 1,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Kontroller alle 250 timer, skift alle 1000 timer/ 12 måneder

NAVREDUKTIONER BAG

Kapacitet: 0,75 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Kontroller alle 8 timer, skift alle 12 måneder/ 1000 timer

NAVREDUKTIONER FOR

Kapacitet: 0,75 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Kontroller alle 8 timer, skift alle 12 måneder/ 1000 timer

GENIE SPOREDE SKOVANHÆNGERE GTH/AGRI GTH-4017 (10645 -> 19295) - PERKINS 1104C-44T



HYDRAULISK SYSTEM

Kapacitet: 150 liter

ANVEND		KLIMA
Normal		Tropisk
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 68	Perlus AF 68	

Kontroller alle 8 timer, skift alle 12 måneder/ 1000 timer

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 46	Perlus AF 46	

Kontroller alle 8 timer, skift alle 12 måneder/ 1000 timer

ANVEND		KLIMA
Normal		Arktisk
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 22	Perlus AF 32	

Kontroller alle 8 timer, skift alle 12 måneder/ 1000 timer

KØLESYSTEM

Kapacitet: 15 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

Kontroller alle 8 timer, skift alle 24 måneder/ 2000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.