

GENIE SPOREDE SKOVANHÆNGERE GTH/AGRI GTH-6622 (11982 ->) - DEUTZ BF4M-2011



MOTOR Deutz BF4M-2011
Kapacitet: 14,5 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40

Kontroller alle 10 timer, skift alle 1 måneder/ 250 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Armado Synth 5W-30

Kontroller alle 10 timer, skift alle 1 måneder/ 250 timer

DIFFERENTIALE BAG
Kapacitet: 5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

DIFFERENTIALE FOR
Kapacitet: 6 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

NAVREDUKTIONER BAG
Kapacitet: 0,7 liter (hvert nav)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

GENIE SPOREDE SKOVANHÆNGERE GTH/AGRI GTH-6622 (11982 ->) - DEUTZ BF4M-2011



NAVREDUKTIONER FOR

Kapacitet: 1,5 liter (hvert nav)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube LS 80W-90

HYDRAULISK SYSTEM

Kapacitet: 90 liter

ANVEND
Normal

KLIMA
Tropisk

PRODUKTANBEFALING 1
Perlus H 68

PRODUKTANBEFALING 2
Perlus AF 68

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Perlus H 46

PRODUKTANBEFALING 2
Perlus AF 46

ANVEND
Normal

KLIMA
Arktisk

PRODUKTANBEFALING 1
Perlus H 22

PRODUKTANBEFALING 2
Perlus AF 32

HYDRAULISK BREMSESYSTEM

Kapacitet: 0,1 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Perlus H 46

PRODUKTANBEFALING 2
Perlus AF 46

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.