

# GIANT LEDDELTE LÆSSEMASKINER

## D331T KUBOTA D1105-T (S068) (2007 OG EFTER)



**MOTOR** Kubota D1105-T  
Kapacitet: 4,25 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2         | PRODUKTANBEFALING 3           |
|-----------------------------|-----------------------------|-------------------------------|
| <b>Kroontrak MTH 10W-30</b> | <b>Synfleet SHPD 10W-40</b> | <b>Multifleet SHPD 10W-40</b> |

*Kontroller alle 8 timer, skift alle 200 timer*

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2         | PRODUKTANBEFALING 3           |
|-----------------------------|-----------------------------|-------------------------------|
| <b>Kroontrak MTH 10W-30</b> | <b>Synfleet SHPD 10W-40</b> | <b>Multifleet SHPD 10W-40</b> |

*Kontroller alle 8 timer, skift alle 50 timer*

**DIFFERENTIALE BAG**  
Kapacitet: 4,5 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1       |  |  |
|---------------------------|--|--|
| <b>Gearlube LS 80W-90</b> |  |  |

*Kontroller alle 50 timer, skift alle 1000 timer*

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

| PRODUKTANBEFALING 1       |  |  |
|---------------------------|--|--|
| <b>Gearlube LS 80W-90</b> |  |  |

*Kontroller alle 50 timer, skift alle 300 timer*

**DIFFERENTIALE FOR**  
Kapacitet: 3,6 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1       |  |  |
|---------------------------|--|--|
| <b>Gearlube LS 80W-90</b> |  |  |

*Kontroller alle 50 timer, skift alle 1000 timer*

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

| PRODUKTANBEFALING 1       |  |  |
|---------------------------|--|--|
| <b>Gearlube LS 80W-90</b> |  |  |

*Kontroller alle 50 timer, skift alle 300 timer*

# GIANT LEDDELTE LÆSSEMASKINER

## D331T KUBOTA D1105-T (S068) (2007 OG EFTER)

**HYDRAULISK SYSTEM**

Kapacitet: 66 liter

## ANVEND

Normal

## KLIMA

Moderat

## PRODUKTANBEFALING 1

**Perlus Biosynth 46**

## PRODUKTANBEFALING 2

**Perlus H 46**

## PRODUKTANBEFALING 3

**Perlus Biosynth 32***Kontroller alle 50 timer, skift alle 1000 timer*

## ANVEND

Første Service

## KLIMA

Moderat

## PRODUKTANBEFALING 1

**Perlus Biosynth 46**

## PRODUKTANBEFALING 2

**Perlus H 46**

## PRODUKTANBEFALING 3

**Perlus Biosynth 32***Skift alle 50 timer***SMØREPUNKTER/NIPLER**

## ANVEND

Normal

## KLIMA

Moderat

## PRODUKTANBEFALING 1

**Labora Grease**

## PRODUKTANBEFALING 2

**Q5 MP Calcep Grease EP 2**

## PRODUKTANBEFALING 3

**MP Lithep Grease EP 2***Skift alle 50 timer***KØLESYSTEM**

Kapacitet: 4,7 liter

## ANVEND

Normal

## KLIMA

All climates

## PRODUKTANBEFALING 1

**Coolant -38 Organic NF**

## PRODUKTANBEFALING 2

**Coolant -26***Kontroller alle 8 timer, skift alle 24 måneder*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.