

GIANT LEDDELTE LÆSSEMASKINER V5002 X-TRA KUBOTA V2203-M (2007 OG EFTER)



MOTOR Kubota V2203-M
Kapacitet: 9,25 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40

Kontroller alle 8 timer, skift alle 200 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40

Kontroller alle 8 timer, skift alle 50 timer

DIFFERENTIALE BAG
Kapacitet: 5,8 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

Kontroller alle 50 timer, skift alle 1000 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

Kontroller alle 50 timer, skift alle 300 timer

DIFFERENTIALE FOR
Kapacitet: 4,8 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

Kontroller alle 50 timer, skift alle 1000 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

Kontroller alle 50 timer, skift alle 300 timer

GIANT LEDDELTE LÆSSEMASKINER V5002

X-TRA KUBOTA V2203-M (2007 OG EFTER)



HYDRAULISK SYSTEM

Kapacitet: 83 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Perlus Biosynth 46	Perlus H 46	Perlus Biosynth 32

Kontroller alle 50 timer, skift alle 1000 timer

ANVEND		KLIMA
Første Service		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Perlus Biosynth 46	Perlus H 46	Perlus Biosynth 32

Skift alle 50 timer

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Skift alle 50 timer

KØLESYSTEM

Kapacitet: 10,1 liter

ANVEND		KLIMA
Normal		All climates
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

Kontroller alle 8 timer, skift alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.