

GRADALL BETJENING AF MATERIEL G6-42P S/N 0160000230 ->



MOTOR

Kapacitet: 14,7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 2

Multifleet SHPD 15W-40

Kontroller alle 10 timer, skift alle 250 timer

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 2

Multifleet SHPD 15W-40

Skift alle 50 timer

DIFFERENTIALE FOR

Kapacitet: 18,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2

Agrifluid HT-Plus

PRODUKTANBEFALING 3

Kroontrak MTH 10W-30

Kontroller alle 250 timer, skift alle 1000 timer

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2

Agrifluid HT-Plus

PRODUKTANBEFALING 3

Kroontrak MTH 10W-30

Skift alle 50 timer

NAVREDUKTIONER BAG

Kapacitet: 1,6 liter (hvert nav)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2

Agrifluid HT-Plus

PRODUKTANBEFALING 3

Kroontrak MTH 10W-30

Kontroller alle 250 timer, skift alle 1000 timer

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2

Agrifluid HT-Plus

PRODUKTANBEFALING 3

Kroontrak MTH 10W-30

Skift alle 50 timer

GRADALL BETJENING AF MATERIEL G6-42P S/N 0160000230 ->



HYDRAULISK SYSTEM

Kapacitet: 163 liter (System), Kapacitet: 75,7 liter (Tank)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2

Agrifluid HT-Plus

PRODUKTANBEFALING 3

Kroontrak MTH 10W-30

Kontroller alle 10 timer, skift alle 1500 timer

KØLESYSTEM

Kapacitet: 14,7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Kontroller alle 50 timer, skift alle 1500 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.