

HAKO/MULTICAR MULTICAR M27TL (4X2)

VW 2.0 TDI (EURO 5)

(WMU2M30E5BW270002 ->)



MOTOR CJDD

Kapacitet: 4,3 liter, Filterkapacitet: 0,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Helar SP LL-03 5W-30

Kontroller alle 8 timer, skift alle 25000 km/ 12 måneder/ 500 timer

DIFFERENTIALE BAG

Kapacitet: 4,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 25000 km/ 24 måneder/ 500 timer

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 2500 km/ 50 timer

GEAR MANUEL W 32 S5-01/DK 5/1

Kapacitet: 3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

SP Gear 5015

PRODUKTANBEFALING 3

Gearlube GL-4 80W

Kontroller alle 25000 km/ 500 timer, skift alle 75000 km/ 24 måneder/ 1500 timer

GEAR MANUEL W 32 S5/Nh7-01/DK 5/1

Kapacitet: 3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

SP Gear 5015

PRODUKTANBEFALING 3

Gearlube GL-4 80W

Kontroller alle 25000 km/ 500 timer, skift alle 75000 km/ 24 måneder/ 1500 timer

HAKO/MULTICAR MULTICAR M27TL (4X2)

VW 2.0 TDI (EURO 5)

(WMU2M30E5BW270002 ->)



HYDRAULISK SYSTEM

Kapacitet: 70 liter (Hydraulisk tank. Dobbelt-kredsløbs hydraulik (Variant 03)), Kapacitet: 25 liter (Hydraulisk tank. Til elektrisk kip-hydraulik EHK), Kapacitet: 70 liter (Hydraulisk tank. Tre-kredsløbs universel hydraulik (Variant 04))

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Perlus H 46	Perlus AF 46

Kontroller alle 50 timer, skift alle 25000 km/ 24 måneder/ 500 timer

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1	
Perlus H 32	

Kontroller alle 50 timer, skift alle 25000 km/ 24 måneder/ 500 timer

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Perlus H 22	Perlus AF 32

Kontroller alle 50 timer, skift alle 25000 km/ 24 måneder/ 500 timer

ANVEND	KLIMA
Biologisk nedbrydelig olie	Moderat

PRODUKTANBEFALING 1	
Perlus Biosynth 46	

Kontroller alle 50 timer, skift alle 25000 km/ 24 måneder/ 500 timer

HYDRAULISK BREMSESYSTEM

Kapacitet: 0,7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	
Drauliquid DOT 5.1	

Kontroller alle 50 timer, skift alle 75000 km/ 24 måneder/ 1500 timer

HYDRAULISK KOBLINGSSYSTEM

Kapacitet: 0,3 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	
Drauliquid DOT 5.1	

Kontroller alle 50 timer, skift alle 75000 km/ 24 måneder/ 1500 timer

HAKO/MULTICAR MULTICAR M27TL (4X2)

VW 2.0 TDI (EURO 5)

(WMU2M30E5BW270002 ->)



SMØREPUNKTER/NIPLER CARDANAKSLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

Skift alle 50 timer

SMØREPUNKTER/NIPLER GENERELT

ANVEND

Normal

KLIMA

Tropisk

PRODUKTANBEFALING 1

HT Q9 High Grade Grease

PRODUKTANBEFALING 2

Labora Grease

PRODUKTANBEFALING 3

Q5 MP Calcep Grease EP 2

Skift alle 50 timer

KØLESYSTEM

Kapacitet: 12 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 12

Kontroller alle 50 timer, skift alle 75000 km/ 24 måneder/ 1500 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.