

HAKO/MULTICAR MULTICAR M31H (4X2) IVECO F1CE3481T (EURO 5) (WMU2M31E5DW000003 ->)



MOTOR Iveco F1CE3481T
Kapacitet: 5,5 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

DIFFERENTIALE BAG

Kapacitet: 4,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 30000 km/ 24 måneder/ 600 timer

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 2500 km/ 50 timer

REDUKTIONSGEARKASSE

Kapacitet: 2,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

SP Gear 5015

PRODUKTANBEFALING 3

Gearlube GL-4 80W

Kontroller alle 30000 km/ 600 timer, skift alle 60000 km/ 24 måneder/ 1200 timer

HAKO/MULTICAR MULTICAR M31H (4X2) IVECO F1CE3481T (EURO 5) (WMU2M31E5DW000003 ->)



HYDRAULISK SYSTEM

Kapacitet: 70 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Perlus Biosynth 46	Perlus H 46

Kontroller alle 50 timer, skift alle 24 måneder/ 30000 km

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Perlus Biosynth 32	Perlus H 32

Kontroller alle 50 timer, skift alle 24 måneder/ 30000 km

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1	
Perlus H 22	

Kontroller alle 50 timer, skift alle 24 måneder/ 30000 km

ANVEND	KLIMA
Biologisk nedbrydelig olie	Moderat

PRODUKTANBEFALING 1	
Perlus Biosynth 46	

Kontroller alle 50 timer, skift alle 24 måneder/ 30000 km

HYDRAULISK BREMSESYSYSTEM

Kapacitet: 0,7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	
Drauliquid DOT 5.1	

Kontroller alle 50 timer, skift alle 60000 km/ 24 måneder/ 1200 timer

SMØREPUNKTER/NIPLER CARDANAKSLER

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Skift alle 50 timer

HAKO/MULTICAR MULTICAR M31H (4X2) IVECO F1CE3481T (EURO 5) (WMU2M31E5DW000003 ->)



SMØREPUNKTER/NIPLER GENERELT

ANVEND		KLIMA
Normal		Tropisk
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
HT Q9 High Grade Grease	Labora Grease	Q5 MP Calcep Grease EP 2

Skift alle 50 timer

KØLESYSTEM

Kapacitet: 15 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Coolant SP 11		

Kontroller alle 50 timer, skift alle 60000 km/ 24 måneder/ 1200 timer

HYDRAULIKSYSTEM STYRING

Kapacitet: 3 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
ATF Dexron II-D	ATF-A	

Kontroller alle 50 timer, skift alle 60000 km/ 24 måneder/ 1200 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.