

# HAMM DOBBELTTROMLEKOMPAKTORER

## DV/HD HD 14 VV KUBOTA V2203-M-E3B

### (H2010001 ->)



**MOTOR** Kubota V2203-M-E3B  
Kapacitet: 9,5 liter (Servicepåfyldning)

| ANVEND         | KLIMA            |
|----------------|------------------|
| Første Service | Middelhavsagtigt |

|                               |  |  |
|-------------------------------|--|--|
| PRODUKTANBEFALING 1           |  |  |
| <b>Multifleet SHPD 20W-50</b> |  |  |

Skift alle 50 timer

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

|                             |                             |                             |
|-----------------------------|-----------------------------|-----------------------------|
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2         | PRODUKTANBEFALING 3         |
| <b>Agrisynth LSP 10W-40</b> | <b>Kroontrak CVT 10W-40</b> | <b>Agrisynth MSP 10W-40</b> |

Skift alle 50 timer

| ANVEND                                                               | KLIMA            |
|----------------------------------------------------------------------|------------------|
| Normal, svovlniveau i brændstof <0,5 %, omgivelsestemperatur >-10° C | Middelhavsagtigt |

|                               |  |  |
|-------------------------------|--|--|
| PRODUKTANBEFALING 1           |  |  |
| <b>Multifleet SHPD 20W-50</b> |  |  |

Skift alle 250 timer

| ANVEND                                                               | KLIMA   |
|----------------------------------------------------------------------|---------|
| Normal, svovlniveau i brændstof <0,5 %, omgivelsestemperatur >-10° C | Moderat |

|                             |                             |                             |
|-----------------------------|-----------------------------|-----------------------------|
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2         | PRODUKTANBEFALING 3         |
| <b>Agrisynth LSP 10W-40</b> | <b>Kroontrak CVT 10W-40</b> | <b>Agrisynth MSP 10W-40</b> |

Skift alle 250 timer

**HYDRAULISK SYSTEM**  
Kapacitet: 33 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Tropisk |

|                     |  |  |
|---------------------|--|--|
| PRODUKTANBEFALING 1 |  |  |
| <b>Perlus H 68</b>  |  |  |

Skift alle 2000 timer

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

|                           |                     |  |
|---------------------------|---------------------|--|
| PRODUKTANBEFALING 1       | PRODUKTANBEFALING 2 |  |
| <b>Perlus Biosynth 46</b> | <b>Perlus H 46</b>  |  |

Skift alle 2000 timer

# HAMM DOBBELTTROMLEKOMPAKTORER DV/HD HD 14 VV KUBOTA V2203-M-E3B (H2010001 ->)



| ANVEND                     |                     | KLIMA   |
|----------------------------|---------------------|---------|
| Normal                     |                     | Koldt   |
| PRODUKTANBEFALING 1        | PRODUKTANBEFALING 2 |         |
| <b>Perlus Biosynth 32</b>  | <b>Perlus H 32</b>  |         |
| Skift alle 2000 timer      |                     |         |
| ANVEND                     |                     | KLIMA   |
| Normal                     |                     | Arktisk |
| PRODUKTANBEFALING 1        |                     |         |
| <b>Perlus H 22</b>         |                     |         |
| Skift alle 2000 timer      |                     |         |
| ANVEND                     |                     | KLIMA   |
| Biologisk nedbrydelig olie |                     | Moderat |
| PRODUKTANBEFALING 1        |                     |         |
| <b>Perlus Biosynth 46</b>  |                     |         |
| Skift alle 2000 timer      |                     |         |
| ANVEND                     |                     | KLIMA   |
| Biologisk nedbrydelig olie |                     | Koldt   |
| PRODUKTANBEFALING 1        |                     |         |
| <b>Perlus Biosynth 32</b>  |                     |         |
| Skift alle 2000 timer      |                     |         |

## KØLESYSTEM

Kapacitet: 9,5 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*