

HAMM DOBBELTTROMLEKOMPAKTORER

DV/HD HD+ 140 VV-HV DEUTZ TCD2012 L04

2V (H1840021 -> 1840053)



MOTOR Deutz TCD 2012 L04 2V
Kapacitet: 11,5 liter (Servicepåfyldning)

ANVEND	KLIMA
Normal, svovlniveau i brændstof <0,5 %, omgivelsestemperatur >-10° C	Middelhavsagtigt

PRODUKTANBEFALING 1		
Multifleet SHPD 20W-50		

Skift alle 500 timer

ANVEND	KLIMA
Normal, svovlniveau i brændstof <0,5 %, omgivelsestemperatur >-10° C	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP 10W-40	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40

Skift alle 500 timer

HYDRAULISK SYSTEM
Kapacitet: 40 liter (Hydrauliktank)

ANVEND	KLIMA
Normal	Tropisk

PRODUKTANBEFALING 1		
Perlus H 68		

Skift alle 2000 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus Biosynth 46	Perlus H 46	

Skift alle 2000 timer

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus Biosynth 32	Perlus H 32	

Skift alle 2000 timer

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1		
Perlus H 22		

Skift alle 2000 timer

HAMM DOBBELTTROMLEKOMPACTORER DV/HD HD+ 140 VV-HV DEUTZ TCD2012 L04 2V (H1840021 -> 1840053)



ANVEND		KLIMA
Biologisk nedbrydelig olie		Moderat
PRODUKTANBEFALING 1		
Perlus Biosynth 46		

Skift alle 2000 timer

ANVEND		KLIMA
Biologisk nedbrydelig olie		Koldt
PRODUKTANBEFALING 1		
Perlus Biosynth 32		

Skift alle 2000 timer

KØLESYSTEM

Kapacitet: 16 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

VIBRATOR

Kapacitet: 13 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.