

HAMM DOBBELTTROMLEKOMPAKTORER

DV/HD HD 90.4 DEUTZ BF4M1013E

(H1530044 ->)



MOTOR Deutz BF4M-1013E
Kapacitet: 12,5 liter (Servicepåfyldning)

ANVEND	KLIMA
Første Service	Middelhavsagtigt

PRODUKTANBEFALING 1		
Multifleet SHPD 20W-50		

Skift alle 50 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP 10W-40	Kroontrak CVT 10W-40	Agrisynth MSP 10W-40

Skift alle 50 timer

ANVEND	KLIMA
Normal, svovlniveau i brændstof <0,5 %, omgivelsestemperatur >-10° C	Middelhavsagtigt

PRODUKTANBEFALING 1		
Multifleet SHPD 20W-50		

Skift alle 500 timer

ANVEND	KLIMA
Normal, svovlniveau i brændstof <0,5 %, omgivelsestemperatur >-10° C	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP 10W-40	Kroontrak CVT 10W-40	Agrisynth MSP 10W-40

Skift alle 500 timer

HAMM DOBBELTTROMLEKOMPAKTORER

DV/HD HD 90.4 DEUTZ BF4M1013E

(H1530044 ->)



HYDRAULISK SYSTEM

Kapacitet: 70 liter (Hydrauliktank)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus HCD 46

Skift alle 2000 timer

ANVEND

Biologisk nedbrydelig olie

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus Biosynth 46

Skift alle 2000 timer

ANVEND

Biologisk nedbrydelig olie

KLIMA

Koldt

PRODUKTANBEFALING 1

Perlus Biosynth 32

Skift alle 2000 timer

KØLESYSTEM

Kapacitet: 21,5 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

VIBRATOR

Kapacitet: 1,2 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.