

HAMM DOBBELTTROMLEKOMPAKTORER

DV/HD HD O70V DEUTZ BF4M1011F

(H1520018 ->)



MOTOR Deutz BF4M-1011F
Kapacitet: 10 liter (Servicepåfyldning)

ANVEND	KLIMA
Første Service	Tropisk

PRODUKTANBEFALING 1		
Multifleet SCD 40		

Skift alle 50 timer

ANVEND	KLIMA
Første Service	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	Multifleet SCD 30

Skift alle 50 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1		
Multifleet SHPD 10W-40		

Skift alle 50 timer

ANVEND	KLIMA
Normal, svovlniveau i brændstof <0,5 %, omgivelsestemperatur >-10° C	Tropisk

PRODUKTANBEFALING 1		
Multifleet SCD 40		

Skift alle 500 timer

ANVEND	KLIMA
Normal, svovlniveau i brændstof <0,5 %, omgivelsestemperatur >-10° C	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	Multifleet SCD 30

Skift alle 500 timer

ANVEND	KLIMA
Normal, svovlniveau i brændstof <0,5 %, omgivelsestemperatur >-10° C	Moderat

PRODUKTANBEFALING 1		
Multifleet SHPD 10W-40		

Skift alle 500 timer

HYDRAULISK SYSTEM
Kapacitet: 50 liter (Hydrauliktank)

HAMM DOBBELTTROMLEKOMPAKTORER

DV/HD HD O70V DEUTZ BF4M1011F

(H1520018 ->)



ANVEND		KLIMA
Normal		Tropisk
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Perlus H 68	Perlus AF 68	Perlus AF 100

Skift alle 2000 timer

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 46	Perlus AF 46	

Skift alle 2000 timer

ANVEND		KLIMA
Normal		Koldt
PRODUKTANBEFALING 1		
Perlus H 32		

Skift alle 2000 timer

ANVEND		KLIMA
Normal		Arktisk
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 22	Perlus AF 32	

Skift alle 2000 timer

ANVEND		KLIMA
Biologisk nedbrydelig olie		Moderat
PRODUKTANBEFALING 1		
Perlus Biosynth 46		

Skift alle 2000 timer

ANVEND		KLIMA
Biologisk nedbrydelig olie		Koldt
PRODUKTANBEFALING 1		
Perlus Biosynth 32		

Skift alle 2000 timer

KØLESYSTEM

Kapacitet: 13 liter (+ køler og varmeapparat)

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.