

HAMM DOBBELTTROMLEKOMPAKTORER

DV/HD HD 075V ASC DEUTZ BF4M2011

(H1730001 ->)



MOTOR Deutz BF4M-2011
Kapacitet: 10 liter (Servicepåfyldning)

ANVEND	KLIMA
Første Service	Middelhavsagtigt

PRODUKTANBEFALING 1
Multifleet SHPD 20W-50

Skift alle 50 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1
Agrisynth LSP 10W-40

PRODUKTANBEFALING 2
Kroontrak CVT 10W-40

PRODUKTANBEFALING 3
Agrisynth MSP 10W-40

Skift alle 50 timer

ANVEND	KLIMA
Normal, svovlniveau i brændstof <0,5 %, omgivelsestemperatur >-10° C	Middelhavsagtigt

PRODUKTANBEFALING 1
Multifleet SHPD 20W-50

Skift alle 500 timer

ANVEND	KLIMA
Normal, svovlniveau i brændstof <0,5 %, omgivelsestemperatur >-10° C	Moderat

PRODUKTANBEFALING 1
Agrisynth LSP 10W-40

PRODUKTANBEFALING 2
Kroontrak CVT 10W-40

PRODUKTANBEFALING 3
Agrisynth MSP 10W-40

Skift alle 500 timer

HYDRAULISK SYSTEM
Kapacitet: 45 liter (Hydrauliktank)

ANVEND	KLIMA
Normal	Tropisk

PRODUKTANBEFALING 1
Perlus H 68

PRODUKTANBEFALING 2
Perlus AF 68

PRODUKTANBEFALING 3
Perlus AF 100

Skift alle 2000 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1
Perlus H 46

PRODUKTANBEFALING 2
Perlus AF 46

Skift alle 2000 timer

HAMM DOBBELTTROMLEKOMPAKTORER DV/HD HD O75V ASC DEUTZ BF4M2011 (H1730001 ->)



ANVEND		KLIMA
Normal		Koldt
PRODUKTANBEFALING 1		
Perlus H 32		
<i>Skift alle 2000 timer</i>		
ANVEND		KLIMA
Normal		Arktisk
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 22	Perlus AF 32	
<i>Skift alle 2000 timer</i>		
ANVEND		KLIMA
Biologisk nedbrydelig olie		Moderat
PRODUKTANBEFALING 1		
Perlus Biosynth 46		
<i>Skift alle 2000 timer</i>		
ANVEND		KLIMA
Biologisk nedbrydelig olie		Koldt
PRODUKTANBEFALING 1		
Perlus Biosynth 32		
<i>Skift alle 2000 timer</i>		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.