

HAMM ENKELTTROMLEKOMPAKTORER

3411 P DEUTZ BF4M2012C (H2060081 ->)



MOTOR Deutz BF4M-2012C

Kapacitet: 9,5 liter (Servicepåfyldning)

ANVEND

Normal, svovlniveau i brændstof <0,5 %, omgivelsestemperatur >-10° C

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SHPD 20W-50

Skift alle 500 timer

ANVEND

Normal, svovlniveau i brændstof <0,5 %, omgivelsestemperatur >-10° C

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrisynth LSP 10W-40

PRODUKTANBEFALING 2

Agrisynth MSP 10W-40

PRODUKTANBEFALING 3

Agridiesel MSP 15W-40

Skift alle 500 timer

DIFFERENTIALE

Kapacitet: 14 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Kontroller alle 250 timer, skift alle 1000 timer

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Skift alle 500 timer

HYDRAULISK SYSTEM

Kapacitet: 50 liter (Hydrauliktank)

ANVEND

Normal

KLIMA

Tropisk

PRODUKTANBEFALING 1

Perlus H 68

Skift alle 2000 timer

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus Biosynth 46

PRODUKTANBEFALING 2

Perlus H 46

Skift alle 2000 timer

HAMM ENKELTTROMLEKOMPACTORER

3411 P DEUTZ BF4M2012C (H2060081 ->)



ANVEND		KLIMA
Normal		Koldt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus Biosynth 32	Perlus H 32	

Skift alle 2000 timer

ANVEND		KLIMA
Normal		Arktisk
PRODUKTANBEFALING 1		
Perlus H 22		

Skift alle 2000 timer

ANVEND		KLIMA
Biologisk nedbrydelig olie		Moderat
PRODUKTANBEFALING 1		
Perlus Biosynth 46		

Skift alle 2000 timer

ANVEND		KLIMA
Biologisk nedbrydelig olie		Koldt
PRODUKTANBEFALING 1		
Perlus Biosynth 32		

Skift alle 2000 timer

SMØREPUNKTER/NIPLER		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

KØLESYSTEM
Kapacitet: 14 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

BANDAGEGEARKASSE

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

VIBRATOR
Kapacitet: 1,6 liter (hver side)

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.