HAMM SINGLE DRUM COMPACTORS 3412 HT P DEUTZ BF4M2012C (H1600458 ->)



ENGINE Deutz BF4M-2012C Capacity: 9,5 liter (Service fill)		
USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1 Multifleet SHPD 20W-50		
Change every 50 hours		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40
Change every 50 hours		
USE		CLIMATE
Normal, fuel sulfur level <0,5 %, am	nbient temperature > -10°C	Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 20W-50		
Change every 500 hours		
USE		CLIMATE
Normal, fuel sulfur level <0,5 %, am	nbient temperature > -10°C	Moderate
, , , , , , , , , , , , , , , , , , , ,		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
	PRODUCT RECOMMENDATION 2 Agrisynth MSP 10W-40	PRODUCT RECOMMENDATION 3 Agridiesel MSP 15W-40
PRODUCT RECOMMENDATION 1		
PRODUCT RECOMMENDATION 1 Kroontrak CVT 10W-40		
PRODUCT RECOMMENDATION 1 Kroontrak CVT 10W-40		
PRODUCT RECOMMENDATION 1 Kroontrak CVT 10W-40 Change every 500 hours DIFFERENTIAL		
PRODUCT RECOMMENDATION 1 Kroontrak CVT 10W-40 Change every 500 hours DIFFERENTIAL Capacity: 14 liter		Agridiesel MSP 15W-40
PRODUCT RECOMMENDATION 1 Kroontrak CVT 10W-40 Change every 500 hours DIFFERENTIAL Capacity: 14 liter USE		Agridiesel MSP 15W-40 CLIMATE
PRODUCT RECOMMENDATION 1 Kroontrak CVT 10W-40 Change every 500 hours DIFFERENTIAL Capacity: 14 liter use Normal		Agridiesel MSP 15W-40 CLIMATE
PRODUCT RECOMMENDATION 1 Kroontrak CVT 10W-40 Change every 500 hours DIFFERENTIAL Capacity: 14 liter USE Normal PRODUCT RECOMMENDATION 1	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40 CLIMATE
PRODUCT RECOMMENDATION 1 Kroontrak CVT 10W-40 Change every 500 hours DIFFERENTIAL Capacity: 14 liter USE Normal PRODUCT RECOMMENDATION 1 Gearlube LS 80W-90	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40 CLIMATE
PRODUCT RECOMMENDATION 1 Kroontrak CVT 10W-40 Change every 500 hours DIFFERENTIAL Capacity: 14 liter use Normal PRODUCT RECOMMENDATION 1 Gearlube LS 80W-90 Check every 250 hours, change every 10	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40 CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Kroontrak CVT 10W-40 Change every 500 hours DIFFERENTIAL Capacity: 14 liter USE Normal PRODUCT RECOMMENDATION 1 Gearlube LS 80W-90 Check every 250 hours, change every 100 USE	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40 CLIMATE Moderate CLIMATE

HYDRAULIC SYSTEM

Change every 500 hours

Capacity: 50 liter (Hydraulic tank)

HAMM SINGLE DRUM COMPACTORS 3412 HT P DEUTZ BF4M2012C (H1600458 ->)



USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus H 68	Perlus AF 68	Perlus AF 100
Change every 2000 hours		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus AF 46	
Change every 2000 hours		
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Perlus H 32		
Change every 2000 hours		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 22	Perlus AF 32	
Change every 2000 hours		
USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		
Change every 2000 hours		
USE		CLIMATE
Biodegradable oil		Cold
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 32		
Change every 2000 hours		

Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Moderate
USE		CLIMATE
GREASE POINTS/NIPPLES		

PRODUCT RECOMMENDATION

HAMM SINGLE DRUM COMPACTORS 3412 HT P DEUTZ BF4M2012C (H1600458 ->)



COOLING SYSTEM

Capacity: 16 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

DRUM GEARBOX

Capacity: 2 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

VIBRATOR

Capacity: 1,6 liter (each side)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.