

# HAMM ENKELTTROMLEKOMPACTORER 3412 P DEUTZ BF4M1013E (H1600018 -> H1600457)



**MOTOR** Deutz BF4M-1013E  
Kapacitet: 12,5 liter (Servicepåfyldning)

| ANVEND         | KLIMA            |
|----------------|------------------|
| Første Service | Middelhavsagtigt |

|                               |  |  |
|-------------------------------|--|--|
| PRODUKTANBEFALING 1           |  |  |
| <b>Multifleet SHPD 20W-50</b> |  |  |

Skift alle 50 timer

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

|                             |                             |                              |
|-----------------------------|-----------------------------|------------------------------|
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2         | PRODUKTANBEFALING 3          |
| <b>Kroontrak CVT 10W-40</b> | <b>Agrisynth MSP 10W-40</b> | <b>Agridiesel MSP 15W-40</b> |

Skift alle 50 timer

| ANVEND                                                               | KLIMA            |
|----------------------------------------------------------------------|------------------|
| Normal, svovlniveau i brændstof <0,5 %, omgivelsestemperatur >-10° C | Middelhavsagtigt |

|                               |  |  |
|-------------------------------|--|--|
| PRODUKTANBEFALING 1           |  |  |
| <b>Multifleet SHPD 20W-50</b> |  |  |

Skift alle 500 timer

| ANVEND                                                               | KLIMA   |
|----------------------------------------------------------------------|---------|
| Normal, svovlniveau i brændstof <0,5 %, omgivelsestemperatur >-10° C | Moderat |

|                             |                             |                              |
|-----------------------------|-----------------------------|------------------------------|
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2         | PRODUKTANBEFALING 3          |
| <b>Kroontrak CVT 10W-40</b> | <b>Agrisynth MSP 10W-40</b> | <b>Agridiesel MSP 15W-40</b> |

Skift alle 500 timer

**DIFFERENTIALE**  
Kapacitet: 14 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

|                           |  |  |
|---------------------------|--|--|
| PRODUKTANBEFALING 1       |  |  |
| <b>Gearlube LS 80W-90</b> |  |  |

Kontroller alle 250 timer, skift alle 1000 timer

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

|                           |  |  |
|---------------------------|--|--|
| PRODUKTANBEFALING 1       |  |  |
| <b>Gearlube LS 80W-90</b> |  |  |

Skift alle 500 timer

**HYDRAULISK SYSTEM**  
Kapacitet: 50 liter (Hydrauliktank)

# HAMM ENKELTTROMLEKOMPACTORER

## 3412 P DEUTZ BF4M1013E (H1600018 -> H1600457)



| ANVEND              |  | KLIMA   |
|---------------------|--|---------|
| Normal              |  | Tropisk |
| PRODUKTANBEFALING 1 |  |         |
| <b>Perlus H 68</b>  |  |         |

Skift alle 2000 timer

| ANVEND                    |                     | KLIMA   |
|---------------------------|---------------------|---------|
| Normal                    |                     | Moderat |
| PRODUKTANBEFALING 1       | PRODUKTANBEFALING 2 |         |
| <b>Perlus Biosynth 46</b> | <b>Perlus H 46</b>  |         |

Skift alle 2000 timer

| ANVEND                    |                     | KLIMA |
|---------------------------|---------------------|-------|
| Normal                    |                     | Koldt |
| PRODUKTANBEFALING 1       | PRODUKTANBEFALING 2 |       |
| <b>Perlus Biosynth 32</b> | <b>Perlus H 32</b>  |       |

Skift alle 2000 timer

| ANVEND              |  | KLIMA   |
|---------------------|--|---------|
| Normal              |  | Arktisk |
| PRODUKTANBEFALING 1 |  |         |
| <b>Perlus H 22</b>  |  |         |

Skift alle 2000 timer

| ANVEND                     |  | KLIMA   |
|----------------------------|--|---------|
| Biologisk nedbrydelig olie |  | Moderat |
| PRODUKTANBEFALING 1        |  |         |
| <b>Perlus Biosynth 46</b>  |  |         |

Skift alle 2000 timer

| ANVEND                     |  | KLIMA |
|----------------------------|--|-------|
| Biologisk nedbrydelig olie |  | Koldt |
| PRODUKTANBEFALING 1        |  |       |
| <b>Perlus Biosynth 32</b>  |  |       |

Skift alle 2000 timer

| SMØREPUNKTER/NIPLER  |                                 |                              |
|----------------------|---------------------------------|------------------------------|
| ANVEND               |                                 | KLIMA                        |
| Normal               |                                 | Moderat                      |
| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |



# HAMM ENKELTTROMLEKOMPACTORER 3412 P DEUTZ BF4M1013E (H1600018 -> H1600457)



## KØLESYSTEM

Kapacitet: 16 liter

### ANVEND

Normal

### KLIMA

Moderat

#### PRODUKTANBEFALING 1

**Coolant -38 Organic NF**

#### PRODUKTANBEFALING 2

**Coolant -26**

*Skift alle 2000 timer*

## TROMLE GEARKASSE

Kapacitet: 2 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

## VIBRATOR

Kapacitet: 1,6 liter (hver side)

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*