

HAMM SINGLE DRUM COMPACTORS 3518

DEUTZ BF6M1013E (H1610017 -> H1610296)



ENGINE Deutz BF6M-1013E
Capacity: 26,5 liter (Service fill)

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Tropical |

PRODUCT RECOMMENDATION 1

Multifleet SCD 40

Change every 50 hours

| USE | CLIMATE |
|-----------------|---------------|
| Initial service | Mediterranean |

PRODUCT RECOMMENDATION 1

Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 2

Multifleet SHPD 15W-40

PRODUCT RECOMMENDATION 3

Multifleet SCD 30

Change every 50 hours

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Moderate |

PRODUCT RECOMMENDATION 1

Multifleet SHPD 10W-40

Change every 50 hours

| USE | CLIMATE |
|---|----------|
| Normal, fuel sulfur level <0,5 %, ambient temperature > -10°C | Tropical |

PRODUCT RECOMMENDATION 1

Multifleet SCD 40

Change every 500 hours

| USE | CLIMATE |
|---|---------------|
| Normal, fuel sulfur level <0,5 %, ambient temperature > -10°C | Mediterranean |

PRODUCT RECOMMENDATION 1

Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 2

Multifleet SHPD 15W-40

PRODUCT RECOMMENDATION 3

Multifleet SCD 30

Change every 500 hours

| USE | CLIMATE |
|---|----------|
| Normal, fuel sulfur level <0,5 %, ambient temperature > -10°C | Moderate |

PRODUCT RECOMMENDATION 1

Multifleet SHPD 10W-40

Change every 500 hours

HAMM SINGLE DRUM COMPACTORS 3518

DEUTZ BF6M1013E (H1610017 -> H1610296)

**DIFFERENTIAL**

Capacity: 14 liter

| USE | | CLIMATE |
|---------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Gearlube LS 80W-90 | | |

Check every 250 hours, change every 1000 hours

| USE | | CLIMATE |
|---------------------------|--|----------|
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Gearlube LS 80W-90 | | |

*Change every 500 hours***HYDRAULIC SYSTEM**

Capacity: 50 liter (Hydraulic tank)

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus HCD 46 | | |

Change every 2000 hours

| USE | | CLIMATE |
|---------------------------|--|----------|
| Biodegradable oil | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus Biosynth 46 | | |

Change every 2000 hours

| USE | | CLIMATE |
|---------------------------|--|---------|
| Biodegradable oil | | Cold |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus Biosynth 32 | | |

*Change every 2000 hours***GREASE POINTS/NIPPLES**

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

HAMM SINGLE DRUM COMPACTORS 3518 DEUTZ BF6M1013E (H1610017 -> H1610296)



COOLING SYSTEM

Capacity: 25 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

DRUM GEARBOX

Capacity: 4 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

VIBRATOR

Capacity: 2 liter (each side)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.