

# HAMM TROMLER MED GUMMIHJUL GRW/HD-TT GRW 15 DEUTZ BF4M2012 (H1780001 ->)



**MOTOR** Deutz BF4M-2012  
Kapacitet: 9,5 liter

ANVEND

Normal, svovlniveau i brændstof <0,5 %, omgivelsestemperatur >-10° C

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

**Multifleet SHPD 20W-50**

*Skift alle 500 timer*

ANVEND

Normal, svovlniveau i brændstof <0,5 %, omgivelsestemperatur >-10° C

KLIMA

Moderat

PRODUKTANBEFALING 1

**Kroontrak CVT 10W-40**

PRODUKTANBEFALING 2

**Agridiesel CRD+ 15W-40**

PRODUKTANBEFALING 3

**Kroontrak MTH 10W-30**

*Skift alle 500 timer*

## DIFFERENTIALE

Kapacitet: 6,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Gearlube LS 80W-90**

*Kontroller alle 250 timer, skift alle 2000 timer*

# HAMM TROMLER MED GUMMIHJUL GRW/HD-TT GRW 15 DEUTZ BF4M2012 (H1780001 ->)



## GEAR POWERSHIFT

Kapacitet: 20,5 liter

| ANVEND              |                     | KLIMA                |
|---------------------|---------------------|----------------------|
| Normal              |                     | Tropisk              |
| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2 | PRODUKTANBEFALING 3  |
| <b>Perlus H 68</b>  | <b>Perlus AF 68</b> | <b>Perlus AF 100</b> |

Skift alle 500 timer

| ANVEND              |                     | KLIMA   |
|---------------------|---------------------|---------|
| Normal              |                     | Moderat |
| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2 |         |
| <b>Perlus H 46</b>  | <b>Perlus AF 46</b> |         |

Skift alle 500 timer

| ANVEND              |  | KLIMA |
|---------------------|--|-------|
| Normal              |  | Koldt |
| PRODUKTANBEFALING 1 |  |       |
| <b>Perlus H 32</b>  |  |       |

Skift alle 500 timer

| ANVEND              |                     | KLIMA   |
|---------------------|---------------------|---------|
| Normal              |                     | Arktisk |
| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2 |         |
| <b>Perlus H 22</b>  | <b>Perlus AF 32</b> |         |

Skift alle 500 timer

## NAVREDUKTIONER

Kapacitet: 5 liter

| ANVEND                    |  | KLIMA   |
|---------------------------|--|---------|
| Normal                    |  | Moderat |
| PRODUKTANBEFALING 1       |  |         |
| <b>Gearlube LS 80W-90</b> |  |         |

Kontroller alle 250 timer, skift alle 2000 timer

# HAMM TROMLER MED GUMMIHJUL

## GRW/HD-TT GRW 15 DEUTZ BF4M2012

### (H1780001 ->)

**HYDRAULISK SYSTEM**

Kapacitet: 6 liter (Hydrauliktank)

| ANVEND              |                     | KLIMA                |
|---------------------|---------------------|----------------------|
| Normal              |                     | Tropisk              |
| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2 | PRODUKTANBEFALING 3  |
| <b>Perlus H 68</b>  | <b>Perlus AF 68</b> | <b>Perlus AF 100</b> |

*Kontroller alle 125 timer, skift alle 500 timer*

| ANVEND              |                     | KLIMA   |
|---------------------|---------------------|---------|
| Normal              |                     | Moderat |
| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2 |         |
| <b>Perlus H 46</b>  | <b>Perlus AF 46</b> |         |

*Kontroller alle 125 timer, skift alle 500 timer*

| ANVEND              |  | KLIMA |
|---------------------|--|-------|
| Normal              |  | Koldt |
| PRODUKTANBEFALING 1 |  |       |
| <b>Perlus H 32</b>  |  |       |

*Kontroller alle 125 timer, skift alle 500 timer*

| ANVEND              |                     | KLIMA   |
|---------------------|---------------------|---------|
| Normal              |                     | Arktisk |
| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2 |         |
| <b>Perlus H 22</b>  | <b>Perlus AF 32</b> |         |

*Kontroller alle 125 timer, skift alle 500 timer***SMØREPUNKTER/NIPLER**

| ANVEND               |                                 | KLIMA                        |
|----------------------|---------------------------------|------------------------------|
| Normal               |                                 | Moderat                      |
| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

**KØLESYSTEM**

Kapacitet: 14 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

# HAMM TROMLER MED GUMMIHJUL GRW/HD-TT GRW 15 DEUTZ BF4M2012 (H1780001 ->)



## TAKTTILPASNING

Kapacitet: 3,6 liter

| ANVEND              |                     | KLIMA                |
|---------------------|---------------------|----------------------|
| Normal              |                     | Tropisk              |
| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2 | PRODUKTANBEFALING 3  |
| <b>Perlus H 68</b>  | <b>Perlus AF 68</b> | <b>Perlus AF 100</b> |

Kontroller alle 2000 timer

| ANVEND              |                     | KLIMA   |
|---------------------|---------------------|---------|
| Normal              |                     | Moderat |
| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2 |         |
| <b>Perlus H 46</b>  | <b>Perlus AF 46</b> |         |

Kontroller alle 2000 timer

| ANVEND              |  | KLIMA |
|---------------------|--|-------|
| Normal              |  | Koldt |
| PRODUKTANBEFALING 1 |  |       |
| <b>Perlus H 32</b>  |  |       |

Kontroller alle 2000 timer

| ANVEND              |                     | KLIMA   |
|---------------------|---------------------|---------|
| Normal              |                     | Arktisk |
| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2 |         |
| <b>Perlus H 22</b>  | <b>Perlus AF 32</b> |         |

Kontroller alle 2000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.