

HANGCHA GAFFELTRUCK N-SERIES

CPCD20N ISUZU C240PKJ



MOTOR Isuzu C240PKJ
Kapacitet: 6,5-7,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Kroontrak MTH 10W-30

PRODUKTANBEFALING 2

Synfleet SHPD 10W-40

PRODUKTANBEFALING 3

Multifleet SHPD 10W-40

Kontroller alle 8 timer, skift alle 100 timer

DIFFERENTIALE FOR
Kapacitet: 8 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 1200 timer

GEAR

Kapacitet: 7 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

SP Matic 2032

PRODUKTANBEFALING 2

ATF Almirol

Skift alle 1200 timer

HYDRAULISK SYSTEM

Kapacitet: 45-50 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Perlus H 32

Skift alle 1200 timer

HYDRAULISK BREMSESYSTEM

Kapacitet: 1,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3

Skift alle 1200 timer

HANGCHA GAFFELTRUCK N-SERIES

CPCD20N ISUZU C240PKJ



SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

Kontroller alle 8 timer, skift alle 100 timer

KØLESYSTEM

Kapacitet: 10-11 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Skift alle 1200 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.