

HAULOTTE TELESKOPISE ARBEJDSPLATFORME H28TJ+ PERKINS 804D-33T (2008-2014)



MOTOR Perkins 804D-33T

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Kontroller alle 10 timer, skift alle 500 timer/ 12 måneder

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Synfleet SHPD 10W-40	Multifleet SHPD 10W-40	

Kontroller alle 10 timer, skift alle 500 timer/ 12 måneder

REDUKTIONSENHED

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Skift alle 250 timer/ 12 måneder

SVINGGEARKASSE

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Skift alle 500 timer/ 12 måneder

HYDRAULISK SYSTEM

Kapacitet: 140 liter (Hydrauliktank)

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1		
Perlus H 68		

Kontroller alle 10 timer, skift alle 1000 timer/ 12 måneder

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 46	Perlus H 32	

Kontroller alle 10 timer, skift alle 1000 timer/ 12 måneder

HAULOTTE TELESKOPISE ARBEJDSPLATFORME H28TJ+ PERKINS 804D-33T (2008-2014)



SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

KØLESYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Kontroller alle 10 timer, skift alle 24 måneder/ 3000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.