

HBM-NOBAS VEJHØVLER BG 130TA-4 (2009 OG EFTER)



MOTOR Perkins
Kapacitet: 18 liter

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Kontroller alle 8 timer, skift alle 12 måneder/ 500 timer

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Synfleet SHPD 10W-40	Multifleet SHPD 10W-40	

Kontroller alle 8 timer, skift alle 12 måneder/ 500 timer

GEAR AUTOMATISK ZF 6WG115 6/3
Kapacitet: 30 liter

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Kontroller alle 50 timer, skift alle 1000 timer

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Synfleet SHPD 10W-40	Multifleet SHPD 10W-40	

Kontroller alle 50 timer, skift alle 1000 timer

ANVEND		KLIMA
Normal		Arktisk
PRODUKTANBEFALING 1		
ATF-A		

Kontroller alle 50 timer, skift alle 1000 timer

HBM-NOBAS VEJHØVLER BG 130TA-4 (2009 OG EFTER)



NAVREDUKTIONER BAG

Kapacitet: 1 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Gearlube Racing 75W-140	Gearlube LS 80W-90	Unigear LS GL-3/GL-5 85W-140

Kontroller alle 500 timer, skift alle 12 måneder/ 2000 timer

ANVEND		KLIMA
Første Service		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Gearlube Racing 75W-140	Gearlube LS 80W-90	Unigear LS GL-3/GL-5 85W-140

Skift alle 500 timer

SELVSPÆRRENDE DIFFERENTIALE BAG Tractech NoSPIN Detroit Locker

Kapacitet: 13,5 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Gearlube Racing 75W-140	Gearlube LS 80W-90	Unigear LS GL-3/GL-5 85W-140

Kontroller alle 500 timer, skift alle 12 måneder/ 2000 timer

ANVEND		KLIMA
Første Service		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Gearlube Racing 75W-140	Gearlube LS 80W-90	Unigear LS GL-3/GL-5 85W-140

Skift alle 500 timer

TANDEMDREV

Kapacitet: 21 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Gearlube Racing 75W-140	Gearlube LS 80W-90	Unigear LS GL-3/GL-5 85W-140

Kontroller alle 500 timer, skift alle 30 måneder/ 4000 timer

HBM-NOBAS VEJHØVLER BG 130TA-4 (2009 OG EFTER)



HYDRAULISK SYSTEM

Kapacitet: 160 liter

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Perlus H 68	Perlus AF 68	Perlus AF 100

Kontroller alle 50 timer, skift alle 30 måneder/ 4000 timer

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 46	Perlus AF 46	

Kontroller alle 50 timer, skift alle 30 måneder/ 4000 timer

ANVEND		KLIMA
Normal		Arktisk
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 22	Perlus AF 32	

Kontroller alle 50 timer, skift alle 30 måneder/ 4000 timer

SMØREPUNKTER/NIPLER KUGLELEJEDREJETAP

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	

Kontroller alle 50 timer

ANVEND		KLIMA
Første Service		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	

Kontroller alle 10 timer

KØLESYSTEM

Kapacitet: 34 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

Kontroller alle 8 timer, skift alle 24 måneder

HBM-NOBAS VEJHØVLER BG 130TA-4

(2009 OG EFTER)

**BREMSESYSYSTEM VÅDE BREMSER**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube Racing 75W-140

PRODUKTANBEFALING 2

Gearlube LS 80W-90

PRODUKTANBEFALING 3

Unigear LS GL-3/GL-5 85W-140*Kontroller alle 12 måneder/ 2000 timer*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.