

# HIDROMEK GRAVEMASKINER MED LARVEBÅND HMK 370LC HD (2011 OG EFTER)



**MOTOR** Isuzu AH-6HK1X  
Kapacitet: 38 liter

**ANVEND**

Normalt, svovlniveau i brændstof <50 ppm

**KLIMA**

Moderat

**PRODUKTANBEFALING 1**

**Agridiesel CRD+ 15W-40**

**PRODUKTANBEFALING 2**

**Synfleet SHPD 10W-40**

**PRODUKTANBEFALING 3**

**Dieselfleet CD+ 15W-40**

Kontroller alle 10 timer, skift alle 500 timer

**ANVEND**

Normal, svovlniveau i brændstof <0,2 % (2000 ppm)

**KLIMA**

Middelhavsagtigt

**PRODUKTANBEFALING 1**

**Multifleet SCD 40**

**PRODUKTANBEFALING 2**

**Multifleet SCD 30**

Kontroller alle 10 timer, skift alle 250 timer

**ANVEND**

Normal, svovlniveau i brændstof <0,2 % (2000 ppm)

**KLIMA**

Moderat

**PRODUKTANBEFALING 1**

**Agridiesel CRD+ 15W-40**

**PRODUKTANBEFALING 2**

**Kroontrak MTH 10W-30**

**PRODUKTANBEFALING 3**

**Synfleet SHPD 10W-40**

Kontroller alle 10 timer, skift alle 250 timer

**ANVEND**

Normal, svovlniveau i brændstof 0,2 - 0,5 % (2000 - 5000 ppm)

**KLIMA**

Middelhavsagtigt

**PRODUKTANBEFALING 1**

**Multifleet SCD 40**

**PRODUKTANBEFALING 2**

**Multifleet SCD 30**

Kontroller alle 10 timer, skift alle 185 timer

**ANVEND**

Normal, svovlniveau i brændstof 0,2 - 0,5 % (2000 - 5000 ppm)

**KLIMA**

Moderat

**PRODUKTANBEFALING 1**

**Agridiesel CRD+ 15W-40**

**PRODUKTANBEFALING 2**

**Kroontrak MTH 10W-30**

**PRODUKTANBEFALING 3**

**Synfleet SHPD 10W-40**

Kontroller alle 10 timer, skift alle 185 timer

**ANVEND**

Normal, svovlniveau i brændstof 0,5 - 1,0 % (5000 - 10000 ppm)

**KLIMA**

Middelhavsagtigt

**PRODUKTANBEFALING 1**

**Multifleet SCD 40**

**PRODUKTANBEFALING 2**

**Multifleet SCD 30**

Kontroller alle 10 timer, skift alle 125 timer

**ANVEND**

Normal, svovlniveau i brændstof 0,5 - 1,0 % (5000 - 10000 ppm)

**KLIMA**

Moderat

**PRODUKTANBEFALING 1**

**Agridiesel CRD+ 15W-40**

**PRODUKTANBEFALING 2**

**Kroontrak MTH 10W-30**

**PRODUKTANBEFALING 3**

**Synfleet SHPD 10W-40**

Kontroller alle 10 timer, skift alle 125 timer

# HIDROMEK GRAVEMASKINER MED LARVEBÅND HMK 370LC HD (2011 OG EFTER)



## HYDRAULISK SYSTEM

Kapacitet: 250 liter (Hydrauliktank), Kapacitet: 455 liter (System)

| ANVEND              |                     | KLIMA            |
|---------------------|---------------------|------------------|
| Normal              |                     | Middelhavsagtigt |
| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2 |                  |
| <b>Perlus H 68</b>  | <b>Perlus AF 68</b> |                  |

Kontroller alle 10 timer, skift alle 2000 timer

| ANVEND              |                     | KLIMA               |
|---------------------|---------------------|---------------------|
| Normal              |                     | Moderat             |
| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2 | PRODUKTANBEFALING 3 |
| <b>Perlus H 46</b>  | <b>Perlus H 32</b>  | <b>Perlus AF 46</b> |

Kontroller alle 10 timer, skift alle 2000 timer

## SMØREPUNKTER/NIPLER

| ANVEND               |                                 | KLIMA                        |
|----------------------|---------------------------------|------------------------------|
| Normal               |                                 | Moderat                      |
| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

Kontroller alle 1 uge/ 8 timer

## KØLESYSTEM

Kapacitet: 39 liter

| ANVEND                        |                     | KLIMA   |
|-------------------------------|---------------------|---------|
| Normal                        |                     | Moderat |
| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2 |         |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>  |         |

Kontroller alle 10 timer, skift alle 2000 timer

## DREJERINGSGEAR

Kapacitet: 36,5 kg

| ANVEND               |                                 | KLIMA                        |
|----------------------|---------------------------------|------------------------------|
| Normal               |                                 | Moderat                      |
| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

Skift alle 500 timer

# HIDROMEK GRAVEMASKINER MED LARVEBÅND HMK 370LC HD (2011 OG EFTER)



## KØREREDUKTIONSENHED

Kapacitet: 10 liter

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Gearlube GL-5 80W-90**

### PRODUKTANBEFALING 2

**Unigear HS GL-3/GL-5 80W-90**

*Skift alle 1000 timer*

## SVINGREDUKTIONSENHED

Kapacitet: 6 liter

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Gearlube GL-5 80W-90**

### PRODUKTANBEFALING 2

**Unigear HS GL-3/GL-5 80W-90**

*Skift alle 2000 timer*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*