

HIDROMEK GRAVEMASKINER MED LARVEBÅND HMK 400LC (2011 OG EFTER)



MOTOR Isuzu AH-6HK1X
Kapacitet: 38 liter

ANVEND	KLIMA
Normalt, svovlniveau i brændstof <50 ppm	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40

Kontroller alle 10 timer, skift alle 500 timer

ANVEND	KLIMA
Normal, svovlniveau i brændstof <0,2 % (2000 ppm)	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Multifleet SCD 40	Multifleet SCD 30	

Kontroller alle 10 timer, skift alle 250 timer

ANVEND	KLIMA
Normal, svovlniveau i brændstof <0,2 % (2000 ppm)	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Kroontrak MTH 10W-30	Synfleet SHPD 10W-40

Kontroller alle 10 timer, skift alle 250 timer

ANVEND	KLIMA
Normal, svovlniveau i brændstof 0,2 - 0,5 % (2000 - 5000 ppm)	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Multifleet SCD 40	Multifleet SCD 30	

Kontroller alle 10 timer, skift alle 185 timer

ANVEND	KLIMA
Normal, svovlniveau i brændstof 0,2 - 0,5 % (2000 - 5000 ppm)	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Kroontrak MTH 10W-30	Synfleet SHPD 10W-40

Kontroller alle 10 timer, skift alle 185 timer

ANVEND	KLIMA
Normal, svovlniveau i brændstof 0,5 - 1,0 % (5000 - 10000 ppm)	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Multifleet SCD 40	Multifleet SCD 30	

Kontroller alle 10 timer, skift alle 125 timer

ANVEND	KLIMA
Normal, svovlniveau i brændstof 0,5 - 1,0 % (5000 - 10000 ppm)	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Kroontrak MTH 10W-30	Synfleet SHPD 10W-40

Kontroller alle 10 timer, skift alle 125 timer

HIDROMEK GRAVEMASKINER MED LARVEBÅND HMK 400LC (2011 OG EFTER)



HYDRAULISK SYSTEM

Kapacitet: 250 liter (Hydrauliktank), Kapacitet: 455 liter (System)

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 68	Perlus AF 68	

Kontroller alle 10 timer, skift alle 2000 timer

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Perlus H 46	Perlus H 32	Perlus AF 46

Kontroller alle 10 timer, skift alle 2000 timer

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Kontroller alle 1 uge/ 8 timer

KØLESYSTEM

Kapacitet: 39 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

Kontroller alle 10 timer, skift alle 2000 timer

DREJERINGSGEAR

Kapacitet: 36,5 kg

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Skift alle 500 timer

HIDROMEK GRAVEMASKINER MED LARVEBÅND HMK 400LC (2011 OG EFTER)



KØREREDUKTIONSENHED

Kapacitet: 10 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 1000 timer

SVINGREDUKTIONSENHED

Kapacitet: 6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 2000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.