

HITACHI GRAVEMASKINER MED LARVEBÅND EX EX 200



MOTOR

Kapacitet: 26,5 liter

ANVEND

Normal

KLIMA

Tropisk

PRODUKTANBEFALING 1

Multifleet SCD 40

Kontroller alle 50 timer, skift alle 500 timer

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SCD 30

Kontroller alle 50 timer, skift alle 500 timer

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 2

Multifleet SHPD 15W-40

Kontroller alle 50 timer, skift alle 500 timer

ANVEND

Normal

KLIMA

Arktisk

PRODUKTANBEFALING 1

Multifleet SCD 10W

Kontroller alle 50 timer, skift alle 500 timer

HYDRAULISK SYSTEM

Kapacitet: 220 liter (Olieskiftskapacitet)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 46

PRODUKTANBEFALING 2

Perlus H 32

Kontroller alle 50 timer, skift alle 2000 timer

SMØREPUNKTER/NIPLER ANDRE

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

Skift alle 100 timer

HITACHI GRAVEMASKINER MED LARVEBÅND EX EX 200



SMØREPUNKTER/NIPLER FRONTLEDPINDE

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

Skift alle 50 timer

SMØREPUNKTER/NIPLER INDRE SVINGGEAR

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

Skift alle 500 timer

SMØREPUNKTER/NIPLER SVINGLEJE

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

Skift alle 500 timer

KØLESYSTEM

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Kontroller alle 8 timer, skift alle 500 timer

KØREREDUKTIONSENHED

Kapacitet: 5,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 250 timer, skift alle 2000 timer

HITACHI GRAVEMASKINER MED LARVEBÅND EX EX 200



PUMPEDREV

Kapacitet: 0,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 250 timer, skift alle 1000 timer

SVINGREDUKTIONSENHED

Kapacitet: 7,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 250 timer, skift alle 2000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.