

# HITACHI GRAVEMASKINER MED LARVEBÅND EX EX 400-5



**MOTOR** Isuzu 6RB1  
Kapacitet: 50 liter

ANVEND  
Normal

KLIMA  
Middelhavsagtigt

PRODUKTANBEFALING 1

**Multifleet SCD 30**

*Kontroller alle 8 timer, skift alle 500 timer*

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Dieselfleet CD+ 15W-40**

PRODUKTANBEFALING 2

**Multifleet SHPD 15W-40**

*Kontroller alle 8 timer, skift alle 500 timer*

**PUMPETRACTION**  
Kapacitet: 2,2 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Multifleet SCD 30**

*Skift alle 1000 timer*

**HYDRAULISK SYSTEM**  
Kapacitet: 480 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Perlus H 46**

*Skift alle 2000 timer*

**SMØREPUNKTER/NIPLER ANDRE**

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Labora Grease**

PRODUKTANBEFALING 2

**Q5 MP Calcep Grease EP 2**

PRODUKTANBEFALING 3

**MP Lithep Grease EP 2**

# HITACHI GRAVEMASKINER MED LARVEBÅND EX EX 400-5



## SMØREPUNKTER/NIPLER FRONTLEDPINDE

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Labora Grease**

PRODUKTANBEFALING 2

**Q5 MP Calcep Grease EP 2**

PRODUKTANBEFALING 3

**MP Lithep Grease EP 2**

## SMØREPUNKTER/NIPLER INDRE SVINGGEAR

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Labora Grease**

PRODUKTANBEFALING 2

**Q5 MP Calcep Grease EP 2**

PRODUKTANBEFALING 3

**MP Lithep Grease EP 2**

## SMØREPUNKTER/NIPLER PINDE TIL SKOVL OG LED

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Labora Grease**

PRODUKTANBEFALING 2

**Q5 MP Calcep Grease EP 2**

PRODUKTANBEFALING 3

**MP Lithep Grease EP 2**

## SMØREPUNKTER/NIPLER SVINGLEJE

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Labora Grease**

PRODUKTANBEFALING 2

**Q5 MP Calcep Grease EP 2**

PRODUKTANBEFALING 3

**MP Lithep Grease EP 2**

## KØREREDUKTIONSENHED

Kapacitet: 12 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Gearlube GL-4 80W-90**

PRODUKTANBEFALING 2

**Unigear HS GL-3/GL-5 80W-90**

*Skift alle 2000 timer*

# HITACHI GRAVEMASKINER MED LARVEBÅND EX EX 400-5



## SVINGREDUKTIONSENHED

Kapacitet: 8,2 liter

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Gearlube GL-4 80W-90**

### PRODUKTANBEFALING 2

**Unigear HS GL-3/GL-5 80W-90**

*Skift alle 1000 timer*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*