

HITACHI TRACKED EXCAVATORS EX EX 60-3 (1995-1998)



ENGINE Nissan BD-3004
Capacity: 12,5 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Multifleet SCD 40

Check every 8 hours, change every 500 hours

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SCD 30

Check every 8 hours, change every 500 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 2

Multifleet SHPD 15W-40

Check every 8 hours, change every 500 hours

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W

Check every 8 hours, change every 500 hours

HYDRAULIC SYSTEM

Capacity: 90 liter (Change capacity)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Perlus H 46

Check every 8 hours, change every 2000 hours

GREASE POINTS/NIPPLES FRONT JOINT PINS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2

Change every 50 hours

HITACHI TRACKED EXCAVATORS EX EX 60-3 (1995-1998)



GREASE POINTS/NIPPLES SWING BEARING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 500 hours

GREASE POINTS/NIPPLES SWING INTERNAL GEAR

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 500 hours

COOLING SYSTEM

Capacity: 10 liter

USE		CLIMATE
Preferred		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Check every 8 hours, change every 24 months/ 4000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 8 hours, change every 500 hours

SWING REDUCTION UNIT

Capacity: 1,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 250 hours, change every 1000 hours

HITACHI TRACKED EXCAVATORS EX EX 60-3 (1995-1998)


TRAVEL REDUCTION UNIT

Capacity: 3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 250 hours, change every 2000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.