

HITACHI GRAVEMASKINER MED LARVEBÅND EX EX 60-5 (1995-1999)



MOTOR Nissan A-BD30
Kapacitet: 12,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2

Synfleet SHPD 10W-40

PRODUKTANBEFALING 3

Dieselfleet CD+ 15W-40

Kontroller alle 8 timer, skift alle 500 timer

HYDRAULISK SYSTEM

Kapacitet: 90 liter (Olieskiftskapacitet)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Perlus H 46

Kontroller alle 8 timer, skift alle 1500 timer

SMØREPUNKTER/NIPLER ANDRE

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

Skift alle 500 timer

SMØREPUNKTER/NIPLER PINDE TIL SKOVL OG LED

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

Skift alle 100 timer

HITACHI GRAVEMASKINER MED LARVEBÅND EX EX 60-5 (1995-1999)

**KØLESYSTEM**

Kapacitet: 18,4 liter

ANVEND		KLIMA
Foretrukket, udvided		Moderat
PRODUKTANBEFALING 1 Coolant SP 15+	PRODUKTANBEFALING 2 Coolant SP 12	

Kontroller alle 8 timer, skift alle 24 måneder/ 4000 timer

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1 Coolant -38 Organic NF	PRODUKTANBEFALING 2 Coolant -26	

*Kontroller alle 8 timer, skift alle 6 måneder***KØREREDUKTIONSENHED**

Kapacitet: 2,5 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1 Gearlube GL-4 80W-90	PRODUKTANBEFALING 2 Unigear HS GL-3/GL-5 80W-90	

*Kontroller alle 250 timer, skift alle 2000 timer***SVINGREDUKTIONSENHED**

Kapacitet: 1,8 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1 Gearlube GL-4 80W-90	PRODUKTANBEFALING 2 Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 250 timer, skift alle 1000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.