

HITACHI GRAVEMASKINER MED LARVEBÅND EX EX 750-5



MOTOR Cummins N14C
Kapacitet: 44 liter

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2
Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 3
Multifleet SHPD 15W-40

Kontroller alle 8 timer, skift alle 250 timer

HYDRAULISK SYSTEM
Kapacitet: 660 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Perlus H 46

Kontroller alle 8 timer, skift alle 2000 timer

SMØREPUNKTER/NIPLER ANDRE

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Labora Grease

PRODUKTANBEFALING 2
Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3
MP Lithep Grease EP 2

Skift alle 50 timer

SMØREPUNKTER/NIPLER INDRE SVINGGEAR

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Labora Grease

PRODUKTANBEFALING 2
Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3
MP Lithep Grease EP 2

Skift alle 500 timer

SMØREPUNKTER/NIPLER NEDERSTE PIND TIL CYLINDER I BOM OG HEJS

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Labora Grease

PRODUKTANBEFALING 2
Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3
MP Lithep Grease EP 2

Skift alle 50 timer

HITACHI GRAVEMASKINER MED LARVEBÅND EX EX 750-5



SMØREPUNKTER/NIPLER PINDE TIL SKOVL OG LED

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Skift alle 10 timer

SMØREPUNKTER/NIPLER SVINGLEJE

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Skift alle 500 timer

KØLESYSTEM

Kapacitet: 87 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

Kontroller alle 8 timer, skift alle 6 måneder

KØREREDUKTIONSENHED

Kapacitet: 21 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 250 timer, skift alle 2000 timer

PUMPEDREV

Kapacitet: 5,3 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Multifleet SCD 30		

Kontroller alle 250 timer, skift alle 1000 timer

HITACHI GRAVEMASKINER MED LARVEBÅND EX EX 750-5



SVINGREDUKTIONSENHED

Kapacitet: 15 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 250 timer, skift alle 1000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.