

HITACHI GRAVEMASKINER MED LARVEBÅND EX EX 8 (1994-1994)



MOTOR Isuzu
Kapacitet: 1,9 liter

ANVEND	KLIMA
Normal	Tropisk

PRODUKTANBEFALING 1

Multifleet SCD 40

Kontroller alle 8 timer, skift alle 100 timer

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SCD 30

Kontroller alle 8 timer, skift alle 100 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 2

Multifleet SHPD 15W-40

Kontroller alle 8 timer, skift alle 100 timer

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1

Multifleet SCD 10W

Kontroller alle 8 timer, skift alle 100 timer

ANVEND	KLIMA
Første Service	Tropisk

PRODUKTANBEFALING 1

Multifleet SCD 40

Kontroller alle 8 timer, skift alle 50 timer

ANVEND	KLIMA
Første Service	Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SCD 30

Kontroller alle 8 timer, skift alle 50 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 2

Multifleet SHPD 15W-40

Kontroller alle 8 timer, skift alle 50 timer

HITACHI GRAVEMASKINER MED LARVEBÅND EX EX 8 (1994-1994)



ANVEND		KLIMA
Første Service		Arktisk
PRODUKTANBEFALING 1		
Multifleet SCD 10W		
<i>Kontroller alle 8 timer, skift alle 50 timer</i>		

HYDRAULISK SYSTEM		
Kapacitet: 13 liter (Olieskiftskapacitet)		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Perlus H 46		
<i>Skift alle 1000 timer</i>		

KØLESYSTEM		
Kapacitet: 2,3 liter		
ANVEND		KLIMA
Foretrukket, udvidet		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant SP 15+	Coolant SP 12	
<i>Kontroller alle 8 timer, skift alle 24 måneder/ 4000 timer</i>		

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	
<i>Kontroller alle 8 timer, skift alle 6 måneder</i>		

DREJEGEAR		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

FRONTLEDPINDE		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

HITACHI GRAVEMASKINER MED LARVEBÅND EX EX 8 (1994-1994)



KØREREDUKTIONSENHED

Kapacitet: 0,33 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90*Skift alle 1000 timer*

SVINGLEJE

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.