

HITACHI GRAVEMASKINER MED LARVEBÅND ZX / ZAXIS ZAXIS / ZX 130LCN- 3 (2008 OG EFTER)



MOTOR Isuzu AJ-4JJ1X
Kapacitet: 17 liter

ANVEND	KLIMA
Normalt, svovlniveau i brændstof > 2000 ppm	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agrisynth LSP Ultra FE 5W-30	Dieselfleet CD+ 15W-40	

Kontroller alle 8 timer, skift alle 250 timer

ANVEND	KLIMA
Normalt, svovlniveau i brændstof < 2000 ppm	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agrisynth LSP Ultra FE 5W-30	Dieselfleet CD+ 15W-40	

Kontroller alle 8 timer, skift alle 500 timer

HYDRAULISK SYSTEM

Kapacitet: 70 liter (Hydrauliktank), Kapacitet: 170 liter (System)

ANVEND	KLIMA
Foretrukket, udvided	Moderat

PRODUKTANBEFALING 1		
Perlus H 46		

Kontroller alle 8 timer, skift alle 5000 timer

SMØREPUNKTER/NIPLER

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 16 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant SP 15+	Coolant SP 12	

HITACHI GRAVEMASKINER MED LARVEBÅND ZX / ZAXIS ZAXIS / ZX 130LCN- 3 (2008 OG EFTER)



KØREREDUKTIONSENHED

Kapacitet: 4 liter (hvert)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 250 timer, skift alle 2000 timer

SVINGREDUKTIONSENHED

Kapacitet: 3,2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 250 timer, skift alle 1000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.