

# HITACHI GRAVEMASKINER MED LARVEBÅND ZX / ZAXIS ZAXIS / ZX 210H (2003-2007)



**MOTOR** Isuzu A6BG1T  
Kapacitet: 25 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Kroontrak MTH 10W-30**

PRODUKTANBEFALING 2

**Synfleet SHPD 10W-40**

PRODUKTANBEFALING 3

**Dieselfleet CD+ 15W-40**

*Kontroller alle 8 timer, skift alle 500 timer*

## HYDRAULISK SYSTEM

Kapacitet: 135 liter (Hydrauliktank), Kapacitet: 200 liter (Total)

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Perlus H 46**

*Kontroller alle 8 timer, skift alle 1500 timer*

## SMØREPUNKTER/NIPLER ANDRE

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Labora Grease**

PRODUKTANBEFALING 2

**Q5 MP Calcep Grease EP 2**

PRODUKTANBEFALING 3

**MP Lithep Grease EP 2**

*Skift alle 250 timer/ 6 måneder*

## SMØREPUNKTER/NIPLER FRONTLEDPINDE

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Labora Grease**

PRODUKTANBEFALING 2

**Q5 MP Calcep Grease EP 2**

PRODUKTANBEFALING 3

**MP Lithep Grease EP 2**

*Skift alle 250 timer/ 6 måneder*

## SMØREPUNKTER/NIPLER INDRE SVINGGEAR

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Labora Grease**

PRODUKTANBEFALING 2

**Q5 MP Calcep Grease EP 2**

PRODUKTANBEFALING 3

**MP Lithep Grease EP 2**

*Skift alle 500 timer*

# HITACHI GRAVEMASKINER MED LARVEBÅND ZX / ZAXIS ZAXIS / ZX 210H (2003-2007)



## SMØREPUNKTER/NIPLER SVINGLEJE

| ANVEND               |                                 | KLIMA                        |
|----------------------|---------------------------------|------------------------------|
| Normal               |                                 | Moderat                      |
| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

*Skift alle 500 timer*

## KØLESYSTEM

Kapacitet: 23 liter

| ANVEND                |                      | KLIMA   |
|-----------------------|----------------------|---------|
| Foretrukket, udvidet  |                      | Moderat |
| PRODUKTANBEFALING 1   | PRODUKTANBEFALING 2  |         |
| <b>Coolant SP 15+</b> | <b>Coolant SP 12</b> |         |

*Kontroller alle 8 timer, skift alle 24 måneder/ 4000 timer*

| ANVEND                        |                     | KLIMA   |
|-------------------------------|---------------------|---------|
| Normal                        |                     | Moderat |
| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2 |         |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>  |         |

*Kontroller alle 8 timer, skift alle 6 måneder*

## KØREREDUKTIONSENHED

Kapacitet: 6,8 liter

| ANVEND                      |                                    | KLIMA   |
|-----------------------------|------------------------------------|---------|
| Normal                      |                                    | Moderat |
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |         |
| <b>Gearlube GL-4 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |         |

*Kontroller alle 250 timer, skift alle 2000 timer*

## PUMPEDREV

Kapacitet: 1 liter

| ANVEND                      |                                    | KLIMA   |
|-----------------------------|------------------------------------|---------|
| Normal                      |                                    | Moderat |
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |         |
| <b>Gearlube GL-4 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |         |

*Kontroller alle 250 timer, skift alle 1000 timer*

# HITACHI GRAVEMASKINER MED LARVEBÅND ZX / ZAXIS ZAXIS / ZX 210H (2003-2007)



## SVINGREDUKTIONSENHED

Kapacitet: 6,2 liter

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Gearlube GL-4 80W-90**

### PRODUKTANBEFALING 2

**Unigear HS GL-3/GL-5 80W-90**

*Kontroller alle 250 timer, skift alle 1000 timer*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*