

# HITACHI GRAVEMASKINER MED LARVEBÅND ZX / ZAXIS ZAXIS / ZX 225 USRLC-5B ISUZU AM-4HK1X STAGE IIIB



**MOTOR** Isuzu AM-4HK1X  
Kapacitet: 23 liter

| ANVEND                                         |                              | KLIMA                               |
|------------------------------------------------|------------------------------|-------------------------------------|
| Alternativ, svovlniveau i brændstof < 0,0015 % |                              | Moderat                             |
| PRODUKTANBEFALING 1                            | PRODUKTANBEFALING 2          | PRODUKTANBEFALING 3                 |
| <b>Agrisynth LSP Ultra FE 5W-30</b>            | <b>Agridiesel MSP 15W-40</b> | <b>Dieselfleet LSP Ultra 10W-30</b> |

Kontroller alle 8 timer, skift alle 500 timer

## HYDRAULISK SYSTEM

Kapacitet: 185 liter (Olieskiftskapacitet)

| ANVEND               |  | KLIMA   |
|----------------------|--|---------|
| Foretrukket, udvidet |  | Moderat |
| PRODUKTANBEFALING 1  |  |         |
| <b>Perlus H 46</b>   |  |         |

Kontroller alle 8 timer, skift alle 5000 timer

## SMØREPUNKTER/NIPLER

| ANVEND               |                                 | KLIMA                        |
|----------------------|---------------------------------|------------------------------|
| Normal               |                                 | Moderat                      |
| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

## KØLESYSTEM

Kapacitet: 25 liter

| ANVEND                |                      | KLIMA   |
|-----------------------|----------------------|---------|
| Normal                |                      | Moderat |
| PRODUKTANBEFALING 1   | PRODUKTANBEFALING 2  |         |
| <b>Coolant SP 15+</b> | <b>Coolant SP 12</b> |         |

## KØREREDUKTIONSENHED

Kapacitet: 6,8 liter

| ANVEND                      |                                    | KLIMA   |
|-----------------------------|------------------------------------|---------|
| Normal                      |                                    | Moderat |
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |         |
| <b>Gearlube GL-4 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |         |

Kontroller alle 500 timer, skift alle 2000 timer

# HITACHI GRAVEMASKINER MED LARVEBÅND ZX / ZAXIS ZAXIS / ZX 225 USRLC-5B ISUZU AM-4HK1X STAGE IIIB



## PUMPEDREV

Kapacitet: 1,6 liter

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Dieselfleet CD+ 15W-40**

### PRODUKTANBEFALING 2

**Multifleet SHPD 15W-40**

*Kontroller alle 250 timer, skift alle 1000 timer*

## SVINGREDUKTIONSENHED

Kapacitet: 6,2 liter

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Gearlube GL-4 80W-90**

### PRODUKTANBEFALING 2

**Unigear HS GL-3/GL-5 80W-90**

*Kontroller alle 500 timer, skift alle 1000 timer*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*