

HITACHI GRAVEMASKINER MED LARVEBÅND ZX / ZAXIS ZAXIS / ZX 280 LC-3



MOTOR Isuzu AH-4HK1X
Kapacitet: 23 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Dieselfleet CD+ 15W-40

Kontroller alle 8 timer, skift alle 500 timer

HYDRAULISK SYSTEM

Kapacitet: 243 liter (Hydrauliktank), Kapacitet: 290 liter (Total)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Perlus H 46

Kontroller alle 8 timer, skift alle 1500 timer

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1

Perlus H 32

Kontroller alle 8 timer, skift alle 1500 timer

SMØREPUNKTER/NIPLER FRONTLEDPINDE

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

Skift alle 250 timer/ 6 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

Skift alle 10 timer

HITACHI GRAVEMASKINER MED LARVEBÅND ZX / ZAXIS ZAXIS / ZX 280 LC-3



SMØREPUNKTER/NIPLER INDRE SVINGGEAR

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Skift alle 500 timer

SMØREPUNKTER/NIPLER SVINGLEJE

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Skift alle 500 timer

KØLESYSTEM

Kapacitet: 26 liter

ANVEND		KLIMA
Foretrukket, udvidet		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant SP 15+	Coolant SP 12	

Kontroller alle 8 timer, skift alle 24 måneder/ 4000 timer

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

Kontroller alle 8 timer, skift alle 6 måneder

KØREREDUKTIONSENHED

Kapacitet: 9,2 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 250 timer, skift alle 2000 timer

HITACHI GRAVEMASKINER MED LARVEBÅND ZX / ZAXIS ZAXIS / ZX 280 LC-3



PUMPEDREV

Kapacitet: 1 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SCD 30

Kontroller alle 250 timer, skift alle 1000 timer

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 2

Multifleet SHPD 15W-40

PRODUKTANBEFALING 3

Multifleet SCD 40

Kontroller alle 250 timer, skift alle 1000 timer

SVINGREDUKTIONSENHED

Kapacitet: 11,7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 250 timer, skift alle 1000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.