

HITACHI GRAVEMASKINER MED LARVEBÅND ZX / ZAXIS ZAXIS / ZX 300



MOTOR Isuzu AA-6HK7X
Kapacitet: 36 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Kroontrak MTH 10W-30

PRODUKTANBEFALING 2

Synfleet SHPD 10W-40

PRODUKTANBEFALING 3

Dieselfleet CD+ 15W-40

Kontroller alle 8 timer, skift alle 500 timer

PUMPETRASSION

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Multifleet SCD 30

HYDRAULISK SYSTEM

Kapacitet: 320 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Perlus H 46

Skift alle 1500 timer/ 12 måneder

SMØREPUNKTER/NIPLER FRONTLEDPINDE

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

SMØREPUNKTER/NIPLER INDRE SVINGGEAR

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

HITACHI GRAVEMASKINER MED LARVEBÅND ZX / ZAXIS ZAXIS / ZX 300



SMØREPUNKTER/NIPLER SVINGLEJE

ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Labora Grease	PRODUKTANBEFALING 2 Q5 MP Calcep Grease EP 2	PRODUKTANBEFALING 3 MP Lithep Grease EP 2

KØREREDUKTIONSENHED

Kapacitet: 9,2 liter

ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Gearlube GL-4 80W-90	PRODUKTANBEFALING 2 Unigear HS GL-3/GL-5 80W-90	

Skift alle 2000 timer

SVINGREDUKTIONSENHED

Kapacitet: 16,3 liter

ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Gearlube GL-4 80W-90	PRODUKTANBEFALING 2 Unigear HS GL-3/GL-5 80W-90	

Skift alle 1000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.