

HITACHI GRAVEMASKINER MED LARVEBÅND ZX / ZAXIS ZAXIS / ZX 50 (2003- 2010)



MOTOR Kubota V2203
Kapacitet: 9 liter

ANVEND
Normal

KLIMA
Middelhavssagtigt

PRODUKTANBEFALING 1
Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 2
Multifleet SHPD 15W-40

PRODUKTANBEFALING 3
Multifleet SCD 30

Kontroller alle 8 timer, skift alle 250 timer

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Kroontrak MTH 10W-30

PRODUKTANBEFALING 2
Synfleet SHPD 10W-40

PRODUKTANBEFALING 3
Multifleet SHPD 10W-40

Kontroller alle 8 timer, skift alle 250 timer

ANVEND
Normal

KLIMA
Arktisk

PRODUKTANBEFALING 1
Multifleet SCD 10W

Kontroller alle 8 timer, skift alle 250 timer

HYDRAULISK SYSTEM

Kapacitet: 84 liter (Olieskiftskapacitet)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Perlus H 46

Kontroller alle 8 timer, skift alle 1000 timer

SMØREPUNKTER/NIPLER

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Labora Grease

PRODUKTANBEFALING 2
Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3
MP Lithep Grease EP 2

HITACHI GRAVEMASKINER MED LARVEBÅND ZX / ZAXIS ZAXIS / ZX 50 (2003- 2010)



KØLESYSTEM

Kapacitet: 5,3 liter

ANVEND

Foretrukket, udvided

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

Kontroller alle 8 timer, skift alle 24 måneder/ 2000 timer

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Kontroller alle 8 timer, skift alle 6 måneder

KØREREDUKTIONSENHED

Kapacitet: 0,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 250 timer, skift alle 1000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.