

HITACHI GRAVEMASKINER MED LARVEBÅND ZX / ZAXIS ZAXIS / ZX 65USB- 5A (2013 OG EFTER)



MOTOR Yanmar 4TNV94L
Kapacitet: 10,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Agrisynth LSP Ultra FE 5W-30

PRODUKTANBEFALING 2

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 3

Kroontrak MTH 10W-30

Kontroller alle 8 timer, skift alle 500 timer

HYDRAULISK SYSTEM

Kapacitet: 60 liter (Hydrauliktank), Kapacitet: 107,5 liter (System)

ANVEND
Foretrukne

KLIMA
Moderat

PRODUKTANBEFALING 1

Perlus H 46

Kontroller alle 8 timer, skift alle 2000 timer

SMØREPUNKTER/NIPLER

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

Skift alle 8 timer

KØLESYSTEM

Kapacitet: 7,4 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

KØREREDUKTIONSENHED

Kapacitet: 0,9 liter (hvert)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 500 timer, skift alle 1000 timer

HITACHI GRAVEMASKINER MED LARVEBÅND ZX / ZAXIS ZAXIS / ZX 65USB- 5A (2013 OG EFTER)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.