

HITACHI GRAVEMASKINER MED LARVEBÅND ZX / ZAXIS ZAXIS / ZX 670 LCH-3



MOTOR Isuzu AH-6WG1XYSA
Kapacitet: 57 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agrisynth LSP Ultra FE 5W-30	Dieselfleet CD+ 15W-40	

Kontroller alle 8 timer, skift alle 500 timer

ANVEND	KLIMA
Normal, svovlindhold i brændstof over 0,2% af massen (2000 ppm)	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agrisynth LSP Ultra FE 5W-30	Dieselfleet CD+ 15W-40	

Kontroller alle 8 timer, skift alle 250 timer

HYDRAULISK SYSTEM

Kapacitet: 380 liter (Hydrauliktank), Kapacitet: 720 liter (System)

ANVEND	KLIMA
Foretrukket, udvidet	Moderat

PRODUKTANBEFALING 1		
Perlus H 46		

Kontroller alle 8 timer, skift alle 4000 timer

SMØREPUNKTER/NIPLER

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Skift alle 50 timer

ANVEND	KLIMA
De første 50 timer	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Skift alle 10 timer

HITACHI GRAVEMASKINER MED LARVEBÅND ZX / ZAXIS ZAXIS / ZX 670 LCH-3

**KØLESYSTEM**

Kapacitet: 57 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12*Kontroller alle 8 timer, skift alle 6 måneder***KØREREDUKTIONSENHED**

Kapacitet: 16 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90*Kontroller alle 250 timer, skift alle 2000 timer***PUMPEDREV**

Kapacitet: 6,2 liter

ANVEND

Normal

KLIMA

Tropisk

PRODUKTANBEFALING 1

Multifleet SCD 40*Kontroller alle 250 timer, skift alle 1000 timer*

ANVEND

Normal

KLIMA

Middelhavsaagtigt

PRODUKTANBEFALING 1

Multifleet SCD 30*Kontroller alle 250 timer, skift alle 1000 timer***SVINGREDUKTIONSENHED**

Kapacitet: 10,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90*Kontroller alle 250 timer, skift alle 1000 timer*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.