

HITACHI GUMMIHJULSLÆSSERE LX/ZW ZW150PL CUMMINS QSB4.5 (2009-2014)



MOTOR Cummins QSB4.5
Kapacitet: 14 liter

ANVEND	KLIMA
Normalt, svovlniveau i brændstof 500-5000 ppm	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Agrisynth LSP Ultra FE 5W-30	Dieselfleet CD+ 15W-40

Kontroller alle 8 timer, skift alle 250 timer

ANVEND	KLIMA
Normalt, svovlniveau i brændstof > 5000 ppm	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Agrisynth LSP Ultra FE 5W-30	Dieselfleet CD+ 15W-40

Kontroller alle 8 timer, skift alle 200 timer

ANVEND	KLIMA
Normalt, svovlniveau i brændstof < 500 ppm	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Agrisynth LSP Ultra FE 5W-30	Dieselfleet CD+ 15W-40

Kontroller alle 8 timer, skift alle 500 timer

DIFFERENTIALE BAG
Kapacitet: 27 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Agrifluid HT-Plus	Agrifluid HT

Skift alle 2000 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Agrifluid HT-Plus	Agrifluid HT

Skift alle 250 timer/ 6 måneder

HITACHI GUMMIHJULSLÆSSERE LX/ZW ZW150PL CUMMINS QSB4.5 (2009-2014)



DIFFERENTIALE FOR

Kapacitet: 27 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

Agrifluid HT

Skift alle 2000 timer

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

Agrifluid HT

Skift alle 250 timer/ 6 måneder

GEAR

Kapacitet: 10 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 10W

Kontroller alle 8 timer, skift alle 1000 timer

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 10W

Skift alle 250 timer/ 6 måneder

HYDRAULISK SYSTEM

Kapacitet: 105 liter

ANVEND

Foretrukket, udvided

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 46

Kontroller alle 8 timer, skift alle 2000 timer

ANVEND

Alternativ (acceptabel)

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus Biosynth 46

PRODUKTANBEFALING 2

Perlus H 46

Kontroller alle 8 timer, skift alle 1500 timer

HITACHI GUMMIHJULSLÆSSERE LX/ZW ZW150PL CUMMINS QSB4.5 (2009-2014)



SMØREPUNKTER/NIPLER		
ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Labora Grease	PRODUKTANBEFALING 2 Q5 MP Calcep Grease EP 2	PRODUKTANBEFALING 3 MP Lithep Grease EP 2

KØLESYSTEM Kapacitet: 25 liter		
ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Coolant SP 15+	PRODUKTANBEFALING 2 Coolant SP 12	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.