

HITACHI GUMMIHJULSLÆSSERE LX/ZW ZW310 MERCEDES-BENZ OM460LA (2006-2014)



MOTOR Mercedes-Benz OM460LA
Kapacitet: 39 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Agrisynth LSP 10W-40	Armado Synth 10W-40

Kontroller alle 8 timer, skift alle 500 timer

ANVEND	KLIMA
Alternativ (acceptabel)	Moderat

PRODUKTANBEFALING 1	
Synfleet SHPD 10W-40	

Kontroller alle 8 timer, skift alle 400 timer

ANVEND	KLIMA
Normalt, svovlniveau i brændstof 8000-18000 ppm	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Agrisynth LSP 10W-40	Armado Synth 10W-40

Kontroller alle 8 timer, skift alle 150 timer

ANVEND	KLIMA
Normalt, svovlniveau i brændstof 3000-8000 ppm	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Agrisynth LSP 10W-40	Armado Synth 10W-40

Kontroller alle 8 timer, skift alle 250 timer

DIFFERENTIALE BAG
Kapacitet: 48 liter (+ navreduktioner)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	
Gearlube LS 80W-90	

Skift alle 2000 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	
Gearlube LS 80W-90	

Skift alle 250 timer/ 6 måneder

HITACHI GUMMIHJULSLÆSSERE LX/ZW ZW310 MERCEDES-BENZ OM460LA (2006-2014)



DIFFERENTIALE FOR

Kapacitet: 48 liter (+ navreduktioner)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Skift alle 2000 timer

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Skift alle 250 timer/ 6 måneder

GEAR + MOMENTOMFORMER

Kapacitet: 36 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 10W

Skift alle 1000 timer

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 10W

Skift alle 250 timer/ 6 måneder

NAVREDUKTIONER BAG

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Skift alle 2000 timer

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Skift alle 250 timer/ 6 måneder

HITACHI GUMMIHJULSLÆSSERE LX/ZW ZW310 MERCEDES-BENZ OM460LA (2006-2014)



NAVREDUKTIONER FOR

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

Skift alle 2000 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

Skift alle 250 timer/ 6 måneder

HYDRAULISK SYSTEM

Kapacitet: 128 liter (Hydrauliktank), Kapacitet: 230 liter (Olieskiftskapacitet)

ANVEND	KLIMA
Foretrukket, udvidet	Moderat

PRODUKTANBEFALING 1		
Perlus H 46		

Kontroller alle 8 timer, skift alle 4000 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 46	Perlus AF 46	

Kontroller alle 8 timer, skift alle 1500 timer

HITACHI GUMMIHJULSLÆSSERE LX/ZW ZW310 MERCEDES-BENZ OM460LA (2006-2014)



SMØREPUNKTER/NIPLER PINDE TIL SKOVL OG LED

ANVEND	KLIMA	
Normal	Moderat	

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Skift alle 500 timer

ANVEND	KLIMA	
De første 250 timer	Moderat	

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Skift alle 50 timer

ANVEND	KLIMA	
De første 50 timer	Moderat	

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Skift alle 10 timer

SMØREPUNKTER/NIPLER PROPELAKSEL

ANVEND	KLIMA	
Normal	Moderat	

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Skift alle 2000 timer

ANVEND	KLIMA	
Krævende	Moderat	

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Skift alle 1000 timer

KØLESYSTEM

Kapacitet: 59 liter

ANVEND	KLIMA	
Normal	Moderat	

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Coolant SP 15+	Coolant SP 12	Coolant SP 11

Kontroller alle 8 timer, skift alle 36 måneder/ 4000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.