

HITACHI GUMMIHJULSLÆSSERE LX/ZW

ZW550-5B ISUZ 6WG1 (2013 OG EFTER)



MOTOR Isuzu 6WG1
Kapacitet: 47 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Agrisynth LSP Ultra FE 5W-30

PRODUKTANBEFALING 2

Agridiesel MSP 15W-40

PRODUKTANBEFALING 3

Dieselfleet LSP Ultra 10W-30

Kontroller alle 8 timer, skift alle 500 timer

DIFFERENTIALE BAG
Kapacitet: 115 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

DIFFERENTIALE FOR
Kapacitet: 115 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

GEAR + MOMENTOMFORMER
Kapacitet: 70 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Multifleet SCD 10W

Kontroller alle 8 timer, skift alle 1000 timer

ANVEND
Første Service

KLIMA
Moderat

PRODUKTANBEFALING 1

Multifleet SCD 10W

Kontroller alle 8 timer, skift alle 250 timer

NAVREDUKTIONER BAG
Kapacitet: 32,5 liter (hvert)

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

NAVREDUKTIONER FOR
Kapacitet: 32,5 liter (hvert)

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

HITACHI GUMMIHJULSLÆSSERE LX/ZW ZW550-5B ISUZ 6WG1 (2013 OG EFTER)



HYDRAULISK SYSTEM

Kapacitet: 295 liter (Olieskiftskapacitet)

ANVEND

Foretrukne

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 46

Kontroller alle 8 timer, skift alle 4000 timer

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 68 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.