

HITACHI VOGNE MED LARVEBÅND EG70R-3



MOTOR Isuzu AH-4HK1X
Kapacitet: 25,5 liter

ANVEND	KLIMA
Normal	Tropisk

PRODUKTANBEFALING 1		
Multifleet SCD 40		

Kontroller alle 8 timer, skift alle 250 timer

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1		
Multifleet SCD 30		

Kontroller alle 8 timer, skift alle 250 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

Kontroller alle 8 timer, skift alle 250 timer

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1		
Multifleet SCD 10W		

Kontroller alle 8 timer, skift alle 250 timer

HYDRAULISK SYSTEM
Kapacitet: 55 liter (Olieskiftskapacitet)

ANVEND	KLIMA
Foretrukket, udvided	Moderat

PRODUKTANBEFALING 1		
Perlus H 46		

Kontroller alle 8 timer, skift alle 2000 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Perlus H 46		

Kontroller alle 8 timer, skift alle 1000 timer

HITACHI VOGNE MED LARVEBÅND EG70R-3



SMØREPUNKTER/NIPLER

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

Skift alle 250 timer/ 6 måneder

KØLESYSTEM

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

Kontroller alle 8 timer, skift alle 24 måneder/ 2000 timer

KØREREDUKTIONSENHED

Kapacitet: 4 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 250 timer, skift alle 1000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.