

# HYDREMA RENDEGRAVER 604 PERKINS

## 1004-40HR (1994-1998)



**MOTOR** Perkins 1004-40HR  
Kapacitet: 5,5 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Tropisk |

PRODUKTANBEFALING 1

**Multifleet SCD 40**

*Kontroller alle 10 timer, skift alle 400 timer*

| ANVEND | KLIMA            |
|--------|------------------|
| Normal | Middelhavsagtigt |

PRODUKTANBEFALING 1

**Dieselfleet CD+ 15W-40**

PRODUKTANBEFALING 2

**Multifleet SHPD 15W-40**

PRODUKTANBEFALING 3

**Multifleet SCD 30**

*Kontroller alle 10 timer, skift alle 400 timer*

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

PRODUKTANBEFALING 1

**Multifleet SHPD 10W-40**

*Kontroller alle 10 timer, skift alle 400 timer*

### DIFFERENTIALE BAG

Kapacitet: 8,3 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

PRODUKTANBEFALING 1

**Agrifluid Synth XHP Ultra**

PRODUKTANBEFALING 2

**Kroontrak MTH 10W-30**

PRODUKTANBEFALING 3

**Agrifluid HT**

*Kontroller alle 200 timer, skift alle 1000 timer/ 12 måneder*

### DIFFERENTIALE FOR

Kapacitet: 8,3 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

PRODUKTANBEFALING 1

**Agrifluid Synth XHP Ultra**

PRODUKTANBEFALING 2

**Kroontrak MTH 10W-30**

PRODUKTANBEFALING 3

**Agrifluid HT**

*Kontroller alle 200 timer, skift alle 1000 timer/ 12 måneder*

# HYDREMA RENDEGRAVER 604 PERKINS

## 1004-40HR (1994-1998)



### GEAR Powershift

Kapacitet: 17 liter, Kapacitet: 12 liter (Olieskiftskapacitet)

| ANVEND                       |  | KLIMA            |
|------------------------------|--|------------------|
| Normal                       |  | Middelhavsagtigt |
| PRODUKTANBEFALING 1          |  |                  |
| <b>Multifleet SCD 20W-20</b> |  |                  |

Kontroller alle 10 timer, skift alle 1000 timer/ 12 måneder

| ANVEND                      |                             | KLIMA                         |
|-----------------------------|-----------------------------|-------------------------------|
| Normal                      |                             | Moderat                       |
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2         | PRODUKTANBEFALING 3           |
| <b>Kroontrak MTH 10W-30</b> | <b>Synfleet SHPD 10W-40</b> | <b>Dieselfleet CD+ 15W-40</b> |

Kontroller alle 10 timer, skift alle 1000 timer/ 12 måneder

| ANVEND                 |  | KLIMA   |
|------------------------|--|---------|
| Normal                 |  | Arktisk |
| PRODUKTANBEFALING 1    |  |         |
| <b>ATF Dexron II-D</b> |  |         |

Kontroller alle 10 timer, skift alle 1000 timer/ 12 måneder

### NAVREDUKTIONER BAG

Kapacitet: 0,6 liter

| ANVEND                           |                             | KLIMA               |
|----------------------------------|-----------------------------|---------------------|
| Normal                           |                             | Moderat             |
| PRODUKTANBEFALING 1              | PRODUKTANBEFALING 2         | PRODUKTANBEFALING 3 |
| <b>Agrifluid Synth XHP Ultra</b> | <b>Kroontrak MTH 10W-30</b> | <b>Agrifluid HT</b> |

Kontroller alle 200 timer, skift alle 1000 timer/ 12 måneder

### NAVREDUKTIONER FOR

Kapacitet: 0,6 liter

| ANVEND                           |                             | KLIMA               |
|----------------------------------|-----------------------------|---------------------|
| Normal                           |                             | Moderat             |
| PRODUKTANBEFALING 1              | PRODUKTANBEFALING 2         | PRODUKTANBEFALING 3 |
| <b>Agrifluid Synth XHP Ultra</b> | <b>Kroontrak MTH 10W-30</b> | <b>Agrifluid HT</b> |

Kontroller alle 200 timer, skift alle 1000 timer/ 12 måneder

# HYDREMA RENDEGRAVER 604 PERKINS

## 1004-40HR (1994-1998)



### HYDRAULISK SYSTEM

Kapacitet: 80 liter

| ANVEND              |  | KLIMA            |
|---------------------|--|------------------|
| Normal              |  | Middelhavsagtigt |
| PRODUKTANBEFALING 1 |  |                  |
| <b>Perlus H 46</b>  |  |                  |

Kontroller alle 40 timer, skift alle 24 måneder/ 2000 timer

| ANVEND              |  | KLIMA   |
|---------------------|--|---------|
| Normal              |  | Moderat |
| PRODUKTANBEFALING 1 |  |         |
| <b>Perlus H 32</b>  |  |         |

Kontroller alle 40 timer, skift alle 24 måneder/ 2000 timer

### SMØREPUNKTER/NIPLER

| ANVEND                  |  | KLIMA   |
|-------------------------|--|---------|
| Normal                  |  | Moderat |
| PRODUKTANBEFALING 1     |  |         |
| <b>MoS2 Grease EP 2</b> |  |         |

### KØLESYSTEM

Kapacitet: 14 liter

| ANVEND                        |                     | KLIMA   |
|-------------------------------|---------------------|---------|
| Normal                        |                     | Moderat |
| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2 |         |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>  |         |

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.