

HYDREMA RENDEGRAVER 806T (KASSE 1990)



MOTOR

Kapacitet: 9 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 2

Multifleet SHPD 15W-40

Kontroller alle 10 timer, skift alle 200 timer

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Kroontrak MTH 10W-30

PRODUKTANBEFALING 2

Synfleet SHPD 10W-40

PRODUKTANBEFALING 3

Multifleet SHPD 10W-40

Kontroller alle 10 timer, skift alle 200 timer

DIFFERENTIALE BAG

Kapacitet: 13,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2

Kroontrak MTH 10W-30

PRODUKTANBEFALING 3

Agrifluid HT

Kontroller alle 200 timer, skift alle 24 måneder/ 2400 timer

DIFFERENTIALE FOR

Kapacitet: 13,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2

Kroontrak MTH 10W-30

PRODUKTANBEFALING 3

Agrifluid HT

Kontroller alle 200 timer, skift alle 24 måneder/ 2400 timer

HYDREMA RENDEGRAVER 806T (KASSE 1990)



GEAR Powershift
Kapacitet: 17 liter, Kapacitet: 10 liter (Olieskiftskapacitet)

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Multifleet SCD 20W-20

Kontroller alle 10 timer, skift alle 1200 timer/ 12 måneder

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Multifleet SCD 10W

Kontroller alle 10 timer, skift alle 1200 timer/ 12 måneder

ANVEND
Normal

KLIMA
Arktisk

PRODUKTANBEFALING 1
ATF Dexron II-D

Kontroller alle 10 timer, skift alle 1200 timer/ 12 måneder

NAVREDUKTIONER BAG
Kapacitet: 4 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2
Kroontrak MTH 10W-30

PRODUKTANBEFALING 3
Agrifluid HT

Kontroller alle 200 timer, skift alle 24 måneder/ 2400 timer

NAVREDUKTIONER FOR
Kapacitet: 4 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2
Kroontrak MTH 10W-30

PRODUKTANBEFALING 3
Agrifluid HT

Kontroller alle 200 timer, skift alle 24 måneder/ 2400 timer

HYDREMA RENDEGRAVER 806T (KASSE 1990)



HYDRAULISK SYSTEM

Kapacitet: 125 liter

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1		
Perlus H 46		

Kontroller alle 40 timer, skift alle 24 måneder/ 2400 timer

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Perlus H 32		

Kontroller alle 40 timer, skift alle 24 måneder/ 2400 timer

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
MoS2 Grease EP 2		

KØLESYSTEM

Kapacitet: 23 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

Kontroller alle 10 timer, skift alle 2400 timer/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.