

# HYDREMA RENDEGRAVER 928C SERIER 2 (KASSE 2005)



**MOTOR** Perkins 1104C-44TA  
Kapacitet: 9 liter

ANVEND  
Normal

KLIMA  
Middelhavssagtigt

PRODUKTANBEFALING 1  
**Agridiesel CRD+ 15W-40**

PRODUKTANBEFALING 2  
**Dieselfleet CD+ 15W-40**

PRODUKTANBEFALING 3  
**Multifleet SHPD 15W-40**

*Kontroller alle 10 timer, skift alle 500 timer*

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Kroontrak MTH 10W-30**

PRODUKTANBEFALING 2  
**Synfleet SHPD 10W-40**

PRODUKTANBEFALING 3  
**Multifleet SHPD 10W-40**

*Kontroller alle 10 timer, skift alle 500 timer*

**DIFFERENTIALE BAG**  
Kapacitet: 14 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Agrifluid Synth XHP Ultra**

PRODUKTANBEFALING 2  
**Kroontrak MTH 10W-30**

PRODUKTANBEFALING 3  
**Agrifluid HT**

*Kontroller alle 200 timer, skift alle 1000 timer/ 12 måneder*

**DIFFERENTIALE FOR**  
Kapacitet: 14 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Agrifluid Synth XHP Ultra**

PRODUKTANBEFALING 2  
**Kroontrak MTH 10W-30**

PRODUKTANBEFALING 3  
**Agrifluid HT**

*Kontroller alle 250 timer, skift alle 1000 timer/ 12 måneder*

# HYDREMA RENDEGRAVER 928C SERIER 2 (KASSE 2005)



**GEAR AUTOMATISK** Clark 6/3  
Kapacitet: 12 liter

| ANVEND                        |                               | KLIMA                         |
|-------------------------------|-------------------------------|-------------------------------|
| Normal                        |                               | Middelhavsagtigt              |
| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2           | PRODUKTANBEFALING 3           |
| <b>Agridiesel CRD+ 15W-40</b> | <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> |

Kontroller alle 10 timer, skift alle 1000 timer/ 12 måneder

| ANVEND                 |  | KLIMA   |
|------------------------|--|---------|
| Normal                 |  | Moderat |
| PRODUKTANBEFALING 1    |  |         |
| <b>ATF Dexron II-D</b> |  |         |

Kontroller alle 10 timer, skift alle 1000 timer/ 12 måneder

**NAVREDUKTIONER BAG**  
Kapacitet: 1,5 liter

| ANVEND                           |                             | KLIMA               |
|----------------------------------|-----------------------------|---------------------|
| Normal                           |                             | Moderat             |
| PRODUKTANBEFALING 1              | PRODUKTANBEFALING 2         | PRODUKTANBEFALING 3 |
| <b>Agrifluid Synth XHP Ultra</b> | <b>Kroontrak MTH 10W-30</b> | <b>Agrifluid HT</b> |

Kontroller alle 250 timer, skift alle 1000 timer/ 12 måneder

**NAVREDUKTIONER FOR**  
Kapacitet: 1,5 liter

| ANVEND                           |                             | KLIMA               |
|----------------------------------|-----------------------------|---------------------|
| Normal                           |                             | Moderat             |
| PRODUKTANBEFALING 1              | PRODUKTANBEFALING 2         | PRODUKTANBEFALING 3 |
| <b>Agrifluid Synth XHP Ultra</b> | <b>Kroontrak MTH 10W-30</b> | <b>Agrifluid HT</b> |

Kontroller alle 250 timer, skift alle 1000 timer/ 12 måneder

# HYDREMA RENDEGRAVER 928C SERIER 2 (KASSE 2005)



## HYDRAULISK SYSTEM

Kapacitet: 145 liter (Olieskiftskapacitet)

| ANVEND              |  | KLIMA            |
|---------------------|--|------------------|
| Normal              |  | Middelhavsagtigt |
| PRODUKTANBEFALING 1 |  |                  |
| <b>Perlus H 46</b>  |  |                  |

Kontroller alle 40 timer, skift alle 24 måneder/ 2000 timer

| ANVEND              |  | KLIMA   |
|---------------------|--|---------|
| Normal              |  | Moderat |
| PRODUKTANBEFALING 1 |  |         |
| <b>Perlus H 32</b>  |  |         |

Kontroller alle 40 timer, skift alle 24 måneder/ 2000 timer

## SMØREPUNKTER/NIPLER

| ANVEND                  |  | KLIMA   |
|-------------------------|--|---------|
| Normal                  |  | Moderat |
| PRODUKTANBEFALING 1     |  |         |
| <b>MoS2 Grease EP 2</b> |  |         |

## KØLESYSTEM

| ANVEND                        |                     | KLIMA   |
|-------------------------------|---------------------|---------|
| Normal                        |                     | Moderat |
| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2 |         |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>  |         |

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.