

# HYSTER GAFFELTRUCK, DIESEL H16.00XM-6 (E019) PERKINS (2000-2006)



**MOTOR** Perkins 1006-60T  
Kapacitet: 17,5 liter

ANVEND  
Normal

KLIMA  
Middelhavsagtigt

PRODUKTANBEFALING 1  
**Agridiesel MSP 15W-40**

PRODUKTANBEFALING 2  
**Agridiesel CRD+ 15W-40**

PRODUKTANBEFALING 3  
**Dieselfleet CD+ 15W-40**

Kontroller alle 8 timer, skift alle 2 måneder/ 500 timer

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Kroontrak MTH 10W-30**

PRODUKTANBEFALING 2  
**Synfleet SHPD 10W-40**

PRODUKTANBEFALING 3  
**Armado Synth 5W-30**

Kontroller alle 8 timer, skift alle 2 måneder/ 500 timer

**DRIVAKSEL TØRBREMSEVERSION**  
Kapacitet: 22,5 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Gearlube GL-5 85W-140**

PRODUKTANBEFALING 2  
**Unigear LS GL-3/GL-5 85W-140**

Kontroller alle 2 måneder/ 500 timer

**DRIVAKSEL VÅDBREMSEVERSION**  
Kapacitet: 23,5 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Gearlube GL-5 85W-140**

PRODUKTANBEFALING 2  
**Unigear LS GL-3/GL-5 85W-140**

Kontroller alle 2 måneder/ 500 timer

**GEAR**  
Kapacitet: 28 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

**HYDRAULISK BREMSESYSTEM TØRBREMSEVERSION**  
Kapacitet: 139 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Multifleet SCD 10W**

Kontroller alle 8 timer, skift alle 12 måneder/ 2000 timer

# HYSTER GAFFELTRUCK, DIESEL H16.00XM-6 (E019) PERKINS (2000-2006)



## HYDRAULISK SYSTEM VÅDE BREMSER

Kapacitet: 139 liter

| ANVEND                           |                          | KLIMA                       |
|----------------------------------|--------------------------|-----------------------------|
| Normal                           |                          | Moderat                     |
| PRODUKTANBEFALING 1              | PRODUKTANBEFALING 2      | PRODUKTANBEFALING 3         |
| <b>Agrifluid Synth XHP Ultra</b> | <b>Agrifluid HT-Plus</b> | <b>Kroontrak MTH 10W-30</b> |

Kontroller alle 8 timer, skift alle 12 måneder/ 2000 timer

## SMØREPUNKTER/NIPLER ANDRE

| ANVEND                  |  | KLIMA   |
|-------------------------|--|---------|
| Normal                  |  | Moderat |
| PRODUKTANBEFALING 1     |  |         |
| <b>MoS2 Grease EP 2</b> |  |         |

Kontroller alle 8 timer, skift alle 2 måneder/ 500 timer

## SMØREPUNKTER/NIPLER LØFTEKÆDE

| ANVEND                   |  | KLIMA   |
|--------------------------|--|---------|
| Normal                   |  | Moderat |
| PRODUKTANBEFALING 1      |  |         |
| <b>Multifleet SCD 30</b> |  |         |

Kontroller alle 8 timer, skift alle 2 måneder/ 500 timer

| ANVEND                   |  | KLIMA   |
|--------------------------|--|---------|
| Første Service           |  | Moderat |
| PRODUKTANBEFALING 1      |  |         |
| <b>Multifleet SCD 30</b> |  |         |

Skift alle 100 timer

## KØLESYSTEM

Kapacitet: 31 liter

| ANVEND                        |                     | KLIMA   |
|-------------------------------|---------------------|---------|
| Normal                        |                     | Moderat |
| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2 |         |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>  |         |

Kontroller alle 8 timer, skift alle 12 måneder/ 2000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.