

HYSTER GAFFELTRUCK, DIESEL H700C H32.00C



MOTOR Perkins TV8.540
Kapacitet: 25 liter

ANVEND	KLIMA
Normal	Tropisk

PRODUKTANBEFALING 1		
Multifleet SCD 30		

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	Multifleet SCD 20W-20

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Multifleet SHPD 10W-40		

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1		
Multifleet SCD 10W		

DIFFERENTIALE DRIVAKSEL
Kapacitet: 55 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	Gearlube GL-5 85W-140

GEAR + MOMENTOMFORMER Clark
Kapacitet: 26 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30

HYSTER GAFFELTRUCK, DIESEL H700C H32.00C



GEAR + MOMENTOMFORMER Funk/Hyster

Kapacitet: 26 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gear Oil Alcat 10W	ATF Dexron II-D	

HYDRAULISK SYSTEM

Kapacitet: 269 liter

ANVEND		KLIMA
Normal		Tropisk
PRODUKTANBEFALING 1		
HDX 20W-20		

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Kroontrak MTH 10W-30	HDX 10W	

HYDRAULISK BREMSESYSTEM

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Drauliquid DOT 3		

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
MoS2 Grease EP 2		

KØLESYSTEM

Kapacitet: 21-42 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

HYSTER GAFFELTRUCK, DIESEL H700C H32.00C



HEJSEKÆDER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

HDX 30

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.