

HYUNDAI GAFFELTRUCK, DIESEL 160D-7 CUMMINS QSB5.9 (2008-2011)



MOTOR Cummins QSB5.9C
Kapacitet: 14,2 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2
Synfleet SHPD 10W-40

PRODUKTANBEFALING 3
Dieselfleet CD+ 15W-40

GEAR POWERSHIFT 3/3
Kapacitet: 16 liter (+ "torque converter")

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2
Synfleet SHPD 10W-40

PRODUKTANBEFALING 3
Dieselfleet CD+ 15W-40

Kontroller alle 50 timer, skift alle 6 måneder/ 1000 timer

ANVEND
Første Service

KLIMA
Moderat

PRODUKTANBEFALING 1
Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2
Synfleet SHPD 10W-40

PRODUKTANBEFALING 3
Dieselfleet CD+ 15W-40

Skift alle 100 timer

HYDRAULISK SYSTEM
Kapacitet: 115 liter

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Perlus H 68

Kontroller alle 10 timer, skift alle 2000 timer

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Perlus H 46

PRODUKTANBEFALING 2
Perlus H 32

Kontroller alle 10 timer, skift alle 2000 timer

HYUNDAI GAFFELTRUCK, DIESEL 160D-7 CUMMINS QSB5.9 (2008-2011)



SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Gear Grease EP 1		

KØLESYSTEM

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

Kontroller alle 50 timer, skift alle 2000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.