

# HYUNDAI GAFFELTRUCKS, ELEKTRISKE B/BC/BCS/BH/BHA/BR/BRJ/BT/BTR/HBF/HBR 25BC-7



## DIFFERENTIALE FOR

Kapacitet: 5,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**SP Gear 1011**

PRODUKTANBEFALING 2

**Syngear TDL 75W-90**

PRODUKTANBEFALING 3

**Gearlube GL-5 80W-90**

## HYDRAULISK SYSTEM

Kapacitet: 24 liter (Hydrauliktank)

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

**Perlus H 68**

*Kontroller alle 10 timer, skift alle 2000 timer*

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Perlus H 46**

PRODUKTANBEFALING 2

**Perlus H 32**

*Kontroller alle 10 timer, skift alle 2000 timer*

## HYDRAULISK BREMSESYSYSTEM

Kapacitet: 0,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Drauliquid DOT 3**

*Kontroller alle 10 timer, skift alle 6 måneder/ 1000 timer*

## SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

**Labora Grease**

PRODUKTANBEFALING 2

**Q5 MP Calcep Grease EP 2**

PRODUKTANBEFALING 3

**MP Lithep Grease EP 2**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Gear Grease EP 1**

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is*

PRODUKTANBEFALING

# HYUNDAI GAFFELTRUCKS, ELEKTRISKE B/BC/BCS/BH/BHA/BR/BRJ/BT/BTR/HBF/HBR 25BC-7



*advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*