

HYUNDAI GAFFELTRUCKS, ELEKTRISKE B/BC/BCS/BH/BHA/BR/BRJ/BT/BTR/HBF/HBR 35B-7



DIFFERENTIALE FOR

Kapacitet: 1,5 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30

HYDRAULISK SYSTEM

Kapacitet: 44,9 liter (Hydrauliktank)

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1		
Perlus H 68		

Kontroller alle 10 timer, skift alle 2000 timer

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 46	Perlus H 32	

Kontroller alle 10 timer, skift alle 2000 timer

HYDRAULISK BREMSESYSTEM

Kapacitet: 0,5 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Perlus H 15		

Kontroller alle 10 timer, skift alle 6 måneder/ 1000 timer

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Gear Grease EP 1		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is

PRODUKTANBEFALING

HYUNDAI GAFFELTRUCKS, ELEKTRISKE B/BC/BCS/BH/BHA/BR/BRJ/BT/BTR/HBF/HBR 35B-7



advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.