

# HYUNDAI GAFFELTRUCKS, LPG HLF 15-5 MITSUBISHI 4G63-32HL (2004-2008)



**MOTOR** Mitsubishi 4G63  
Kapacitet: 7,5 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2         |
|----------------------|-----------------------------|
| <b>Asyntho 5W-30</b> | <b>Synfleet SHPD 10W-40</b> |

Kontroller alle 10 timer, skift alle 200 timer

**DIFFERENTIALE FOR**  
Kapacitet: 5 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |
|-----------------------------|------------------------------------|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |

Kontroller alle 1 måneder/ 250 timer, skift alle 6 måneder/ 1000 timer

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |
|-----------------------------|------------------------------------|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |

Skift alle 50 timer

**GEAR POWERSHIFT 1/1**  
Kapacitet: 6,6 liter (+ "torque converter")

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2 |
|----------------------|---------------------|
| <b>SP Matic 2032</b> | <b>ATF Almirol</b>  |

Kontroller alle 50 timer, skift alle 6 måneder/ 1000 timer

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2 |
|----------------------|---------------------|
| <b>SP Matic 2032</b> | <b>ATF Almirol</b>  |

Skift alle 100 timer

# HYUNDAI GAFFELTRUCKS, LPG HLF 15-5

## MITSUBISHI 4G63-32HL (2004-2008)



### HYDRAULISK SYSTEM

Kapacitet: 35 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

**Perlus H 68**

*Kontroller alle 10 timer, skift alle 2000 timer*

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Perlus H 46**

PRODUKTANBEFALING 2

**Perlus H 32**

*Kontroller alle 10 timer, skift alle 2000 timer*

### HYDRAULISK BREMSESYSTEM

Kapacitet: 0,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Drauliquid DOT 3**

*Kontroller alle 10 timer, skift alle 6 måneder/ 1000 timer*

### SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

**Labora Grease**

PRODUKTANBEFALING 2

**Q5 MP Calcep Grease EP 2**

PRODUKTANBEFALING 3

**MP Lithep Grease EP 2**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Gear Grease EP 1**

### KØLESYSTEM

Kapacitet: 17 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Coolant -38 Organic NF**

PRODUKTANBEFALING 2

**Coolant -26**

*Kontroller alle 50 timer, skift alle 2000 timer*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is*

PRODUKTANBEFALING

# HYUNDAI GAFFELTRUCKS, LPG HLF 15-5 MITSUBISHI 4G63-32HL (2004-2008)



*advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*